



Open small storage tank 5 liters 2kW OT - Small storage water heater 5l AEG Hoz5comf.#222154



EHT AEG
AEG Hoz5comf.#222154
222154
4041056023076 EAN/GTIN

1221,54 CNY excl. VAT**
plus shipping

 **15-16 days* (CHN)**

Open small storage tank 5 liters 2kW ÜT AEG Hoz5comf.222154, energy efficiency class=A, energy efficiency class spectrum=A to G, material of the boiler=plastic, material of the jacket=plastic, volume of the container=5 l, nominal power=2 kW, connection voltage=230 V, three-phase version=no, frequency=50 Hz, embodiment=oversink, pedestal/undermount boiler=no, with off-peak mode=no, applicable with normal water pressure=yes, duo version=no, suitable for boiling water=no, warm-up time of 10 °C - 65 °C=10 min, tapping performance at 60 °C, continuous operation=5 l/min, wall installation=yes, horizontal placement=no, vertical placement=yes, KIWA test seal=no, with temperature display=no, temperature limitation= yes, with circulation connection=no, max. permissible operating pressure=0 bar, with fitting=no, with pressure reducing valve=no, with thermometer=no, with cleaning opening=no, protective anode=no, height=443 mm, width=263 mm, depth =242 mm, cold drinking water connection=external thread, nominal internal diameter Diameter of cold drinking water=3/8 inch (10), hot water connection=external thread, tap connection=external thread, degree of protection (IP)=IP24, hot water energy efficiency=38%, tap profile=XXS, small storage tank, capacity 5 litres, for above-table installation. Modern, attractive design. Stepless temperature selection from approx. 35 °C to 85 °C with energy-saving setting ", E" at 40 °C and ", e" at 60 °C. Temperature selection limitation on the rotary knob to 45 °C / 55 °C / 65 °C possible. High-quality thermal insulation, stand-by power consumption of only 0.23 kWh/24h. Safety temperature limiter that can be reset by pulling the mains plug. Connection cable with safety plug, approx. 0.6 m. VDE/GS mark, radio protection mark/EMC. Danger! Application note: This article is a pressureless device (maximum permissible operating pressure = 0 bar). It can only be used with non-pressurized fittings (low-pressure fittings). Please note the difference between high pressure and low pressure fittings. The high-pressure faucet mixes the water inside the faucet. The low-pressure fitting is connected to a water tank (boiler) and has 3 connections. When the water is heated in the storage tank, it expands, which can lead to dripping in the fitting.

YOUR ADVANTAGES

 **WORLDWIDE TRADE**
Corporate video eibmarkt®

 **COMPLAINTS HANDLING**
Obliging and 100% safely

 **SHORT DELIVERY TIME**
Warehousing

 **99% CUSTOMER SATISFACTION**
> 500,000 customers worldwide

 **25 YEARS OF EXPERIENCE**
In worldwide mail order

 **REFUND**
Within 14 days

 **DHL TRACK & TRACE**
Shipment tracking

 **ORDER LIVE CHAT**
With order history

 **DATA PROTECTION**
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

