



CombiController V50 3+1 in the housing - Combined arrester for power systems VG-V50-3+NPE-280



OBO
VG-V50-3+NPE-280
5093596
4012196423224 EAN/GTIN

2337,58 CNY excl. VAT**
plus shipping

 15-16 days* (CHN)

CombiController V50 3+1 in housing VG-V50-3+NPE-280 TN system type, TN-C system type, TN-CS system type, TN-S system type, TT system type, number of poles 3, lightning impulse current (10/350 μ s) 12.5kA, maximum continuous voltage AC 280V, maximum continuous voltage DC 350V, nominal voltage AC 230V, protection level 1.3kV, protection level LN 1.3kV, protection level N-PE 1.3kV, follow current extinguishing capability 0.1kA, max. conductor cross-section solid (solid/stranded) 35mm², Max. conductor cross-section flexible (finely stranded) 35mm², type of installation pre-assembled in the housing, size other, optical signalling on the device, test class type 1 and 2, system solution for lightning current and overvoltage protection of AC systems. The V50 combined lightning current arrester made of halogen-free plastic is suitable for lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305). The modular, pluggable arresters are characterized by a dynamic disconnect device and an optical status display. The NPE variant is also equipped with a heavy-duty spark gap between the neutral and protective conductors. The CombiController is particularly suitable for lightning protection equipotential bonding for buildings of lightning protection class III and IV. The lightning current discharge capacity is 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total. The vibration-proof latching and the voltage and type coding ensure safety and avoid mixing up upper and lower parts. The wedge-shaped design of the contacts makes it easy to insert and even easier to remove the upper parts. Additional technical product information can be called up quickly and easily using the QR code on the rating plate using mobile devices.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

