



Hot water tank open system - Boiler electric VEN 5 U plus 5L U



Vaillant
VEN 5 U plus 5L U
0010021140
4024074802106 EAN/GTIN

623,92 CNY excl. VAT**
plus shipping



4-5 days* (CHN)

Hot water storage tank open system VEN 5 U plus 5L U energy efficiency class A, energy efficiency class spectrum A+ to F, material of the boiler plastic, material jacket plastic, volume of the container 5l, nominal power 2kW, connection voltage 230 ... 230V, frequency 50 Hz, hanging version, Warm-up time from 10 °C - 65 °C 9 min, tapping capacity at 60 °C, continuous operation 5 l/min, vertical placement, temperature limitation, max. permissible operating pressure 0 bar, with cleaning opening, height 400 mm, width 140 mm, depth 232 mm, connection for cold drinking water external thread, Nominal inner diameter of cold drinking water 3/8 inch (10), connection of hot water external thread, nominal inner diameter of hot water connection 3/8 inch (10), degree of protection (IP) IP24, tapping profile XXS, VEN 5/7 U plus electric storage device without pressure under table Product advantages - low pressure under table -Wall storage tank - easy installation with 230 V connection cable with Schuko plug - energy-saving setting at 60 degrees C - frost protection function - consumption that can be activated Protection equipment - water tank made of polypropylene - temperature controller continuously adjustable from 7 to 85 degrees C - splash water protection (IP 24 D) and protective insulation - safety temperature limiter resettable nominal capacity 5 l connected load 2 kW mains voltage 1/N/PE 230 V/50 Hz mixed water volume from 40 degrees C 9.5 l cold/hot water connection R 3/8 height/width/depth 400/240/230 mm weight (filled) 9 kg Seasonal hot water preparation Danger! Application note: This article is a pressureless device (maximum permissible operating pressure = 0 bar). It can only be used with non-pressurized fittings (low-pressure fittings). Please note the difference between high pressure and low pressure fittings. The high-pressure faucet mixes the water inside the faucet. The low-pressure fitting is connected to a water tank (boiler) and has 3 connections. When the water is heated in the storage tank, it expands, which can lead to dripping in the fitting.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

