

×

https://www.eibabo.cn/vaillant/pressure-resistant-hot-water-tank-boiler-electric-veh-50-7-pro-eb142014 34



Pressure-resistant hot water tank - Boiler electric VEH 50/7 pro

Vaillant VEH 50/7 pro 0010016657 4024074755815 EAN/GTIN

4431,20 CNY excl. VAT\*\*

plus shipping bulky item



Pressure-resistant hot water tank VEH 50/7 per energy efficiency class C, energy efficiency class spectrum A to G, boiler material steel, jacket material steel, volume of the tank 50l, nominal output 6kW, connection voltage 230 ... 400V, three-phase version, frequency 50 Hz, hanging version, With off-peak mode, can be used with normal water pressure, connection to a hot water pipe, warm-up time from 10 °C - 65 °C 30 min, tapping capacity at 60 °C, continuous operation 20 l/min, vertical placement, temperature limitation, max. permissible operating pressure 6 bar, with cleaning opening, protective anode, Height 678mm, width 504mm, depth 450mm, diameter 504mm, cold drinking water connection male thread, nominal inside diameter tool drinking water 1/2 inch (15), hot water connection male thread, nominal inside diameter tool drinking water 1/2 inch (15), protection class (IP) IP25, tapping profile M, VEH 50/7 per electric hot water tank closed system, wall-mounted Product advantages - Minimum stand-by energy consumption pleasure through highly efficient thermal insulation - rapid heating for additional hot water requirements - anti-scald protection that can be activated - anti-freeze function - connected load adjustable by moving jumpers Equipment - universal heating flange for single-circuit, dual-circuit and boiler operation - temperature controller infinitely adjustable from 7 to 85 degrees C - high-quality storage enamelling and stainless steel radiators with long Service life - Protection against water jets IP25 enables unrestricted installation in protection area I - Integrated ball valve for quick emptying Nominal capacity 50 I Permissible operating pressure 6 bar Standby heat loss at 65 °C (24 h) 0.85 kWh Mixed water volume at 40 °C 96 I cold/ Hot water connection R 1/2 Height/width/depth 678/504/450 mm Weight unpacked 30 kg Weight ready for use 80 kg Seasonal hot water preparation

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

