

## Item Number EB12700692

https://www.eibabo.cn/wago/installation-floor-clamp-gray-I-I-installation-terminal-block-5-2mm-20a-200 3-6642-eb12700692

## Installation floor clamp gray L/L - Installation terminal block 5,2mm 20A 2003-6642

×



2003-6642 4050821322047 EAN/GTIN

18,66 CNY excl. VAT\*\*

plus **shipping** 



4-5 days\* (CHN)

Multi-level installation terminal 4mm² gray L/L 2003-6642 Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section, finely stranded without ferrule 0.25... 4mm², Connectable conductor cross-section for con section, finely stranded with ferrule 0.75...2.5mm², Connectable conductor cross-section, solid 0.75...4mm², Connectable conductor cross-section stranded 0.25...2.5mm², rated current In 20A, rated voltage 400V, design of electrical connection 1 spring-loaded connection, design of electrical connection 2 spring-loaded connection, connection position at the top, number of potentials 3, mounting type DIN rail TH35, material of the insulating body thermoplastic, operating temperature 105. .. 105°C, flammability class of the insulating material according to UL 94 V0, width/grid dimension 5.2mm, height with the lowest installation type 44.3mm, length 110mm, end plate required, basic color grey, multi-level installation terminal 4 mm2 L/L Push-in CAGE CLAMP® Gray

## YOUR ADVANTAGES



**WORLDWIDE TRADE** Corporate video eibmarkt®



**COMPLAINTS HANDLING** Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE



In worldwide mail order



REFUND Within 14 days



**DHL TRACK & TRACE** Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- \* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

