

Item Number EB13216645

25.04.2024/16:46

×

https://www.eibabo.cn/evn/p-led-cob-spot-with-ground-spike-24vdc-5w-ip67-downlight-spot-floodlight-0 x0w-pc-670502-alu-mt-eb13216645



## P-LED COB spot with ground spike 24VDC 5W IP67 -Downlight/spot/floodlight 0x0W PC 670502 alu-mt

EVN PC 670502 alu-mt PC670502 4037293013284 EAN/GTIN

## 548,96 CNY excl. VAT\*\*

plus shipping

5-16 days\* (CHN)

P-LED COB spot with ground spike 24VDC 5W 3000K IP67 PC 670502 alu-mt Suitable for surface mounting, Suitable for wall mounting, Suitable for ceiling mounting, Suitable for pedestal/floor mounting, Suitable for clamp mounting, Adjustability can be rotated and pivoted, LED bulbs cannot be replaced, With lamp, suitable for number of lamps 0, housing material aluminium, surface untreated, housing color aluminium, cover material transparent glass, type of voltage DC, nominal voltage 24 ... 24V, nominal LED current at constant current 0mA, control gear LED control gear voltage-controlled, dimming dependent from control gear, highly specular reflector, reflector light distributor, symmetrical light distribution, beam angle medium beam 21-40°, light emission direct, type of protection (IP) IP67, protection class III, suitable for lamp power 0W, max. system power 5W, light color white, color temperature 3000 ... 3000K, luminous flux 300 ... 3001m, rated luminous flux according to IEC 62722-2-1 3001m, width 85mm, Height/depth 110mm, length 117mm, outer diameter 62mm, number of poles 2, conductor cross-section 0.75mm², connection type other, light cont uptual blam. Height/depth 110mm, length 117mm, outer diameter 62mm, number of poles 2, conductor cross-section 0.75mm², connection type other, light can either be mounted directly on the surface using the mounted bracket, or optionally with the supplied ground spike on a soft surface will. There is a 3 m long connecting cable with a plug for the IP44 plug-in system on the radiator. Cable entry into the light is via a cable gland. Thanks to the preparation for the plug-in system, larger systems can also be installed quickly and easily without any problems. With the ground spike mounted, the light has a rotation range of 90°. The swivel angle of the lamp is 45°. The ground spike has a length of 170mm.

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

