https://www.eibabo.cn/metz/din-rail-module-category-6-1xrj45-incl.-module-rj45-8-8-jack-tn-e-datmod-reg-lgr-eb14506795

DIN rail module, category 6 1xRJ45, incl. module - RJ45 8(8) jack TN E-DATmod-REG-lgr

Metz
TN E-DATmod-REG-lgr
1309426003-E-90
4250184118060 EAN/GTIN

125,87 CNY excl. VAT**

plus **shipping**

4-5 days* (CHN)

DIN rail module, Cat.6 1xRJ45, incl. Module TN E-DATmod-REG-lgr Socket version (Jack), connector type RJ45 8(8), shielded, category 6, suitable for round cables, suitable for solid conductors, other colors, universal data connection unit RJ45 1 port for stackable DIN rail installation, width 1TE (> 18mm) DIN 42880, protection class I or II depending on the type of installation. Protection class IP 20, category 6, 500 MHz link tested version for data transfer rates up to 10 GBit according to IEEE 802.3an made of die-cast zinc, refined surfaces, with individually shielded RJ45 socket, module housing consisting of only two parts, large-area shield connection with spring-loaded, captive shield connection clamp, from the shield connection Separate strain relief, for connecting category 6A, 7 and 7A cables. Compliance with category 6 12C-de-embedded according to ISO/IEC 11801:2008 Ed.2.1, EN 50173-1:2007 certified by an accredited testing laboratory, PVP certified (continuous quality control) especially with regard to transmission bandwidths by an accredited testing laboratory. Compliance with the 4-connector channel link class EA / 500 MHz on all pair assignments according to ISO/IEC 11801:2008 Ed.2.1 and TIA/EIA 568B.2-10 certified by an accredited testing laboratory, compliance with the permanent link class EA / 500 MHz on all pair assignments certified according to 2nd FPDAM 2 to ISO/IEC 11801 AMD2 (2009-04) and TIA/EIA-568-C.2 (2009-08) by an accredited testing laboratory, for 10BaseT, Token Ring, FDDI (TP -DDI), 100BaseT, ATM 155 MBit/s, Gigabit Ethernet, 10Gigabit Ethernet, suitable for Power over Ethernet (PoE and PoE plus), potential equalization via spring contact to the application, additional connection for potential equalization with flat plug 2.8 mm, metal and plastic parts are recyclable, RoHS-compliant, evidence from the manufacturer must be enclosed.

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online