https://www.eibabo.cn/telegaertner/mini-distributor-category-6a-mpd12-h-unshielded-patch-panel-copper-12x-rj45-8-8-j02022a0054-eb14527009

Mini distributor category 6A MPD12-H unshielded - Patch panel copper 12x RJ45 8(8) J02022A0054

Telegärtner
J02022A0054
4018359368111 EAN/GTIN

625,24 CNY excl. VAT**
plus **shipping**

15-16 days* (CHN)

Mini distributor Cat.6A MPD12-H unshielded J02022A0054 Number of sockets/couplings 12, suitable for number of sockets/couplings 12, connector type RJ45 8(8), shielded, category 6 (IEC), connection type LSA, color gray, RAL number 7035, mounting type wall mounting, height 37mm, width 255mm, depth 118mm, small networks do not necessarily require 19 inch cabinets or large wall distributors. Simple, cost-effective distributors are required that can be installed discreetly and inconspicuously. The compact distributor housing can be mounted on the wall, under the desk, in furniture and, thanks to the integrated adapter, also on TH35 mounting rails in accordance with DIN EN 60715. The MPD12 mini distributor in LSA version of category 6A - with component certificate according to ISO/IEC 11801 - is available for the highest transmission rates up to and including 10 Gbit/s. The RJ45 sockets are designed for at least 750 mating cycles with RJ45/RJ11/RJ12 plugs and are also suitable for applications such as PoE+ in accordance with IEEE 802.3at. 360 degree shield contact (shielded version) directly on the circuit board using a clamp without additional twisting of the shielding braid, shielding hood made of stainless steel, connection of the wires via LSA Plus insulation displacement terminals with color coding according to EIA/TIA 568A and B, easy to connect if the twisted route is adhered to Connection wires to a maximum of 13 mm, Cat.6A (ISO/IEC) & Cat.6A versions with contact overbending protection: suitable for 6-(RJ11/12) and 8-pin connectors (RJ45), can be inserted alternately into the connector without additional assembly effort MJ sockets are used, drawer versions 3 HU/7 TE with 6xRJ45 and 3 HU/10 TE with 12xRJ45, front panel anodized aluminum, housing made of thermoplastic, halogen-free, with anti-slip feet, cable strain relief using the enclosed cable ties without screws and special tools, circuit board mounted horizontally, shielded versions have an internal metal shielding housing. In addition, a PE cable (with M4 screw) can be attached to the circuit board, mini-distributor MPD6, MPD8 MPD12 with 6, 8 or 12 RJ45 connection sockets on a common circuit board, mini-distributor MPD8 AMJ/UMJ and MPD12 AMJ/UMJ for 8 or 12 AM-S/AMJ/UMJ modules and couplings, tool-free attachment of the shielding hood (shielded version), version: unshielded, without shielding hood, also for ISDN/Tel. suitable, color: light gray RAL 7035, MPD12-H K Cat.6A

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online