×



Item Number EB12902385

https://www.eibabo.cn/siemens/circuit-breaker-cl.20-a-release-18-25a-motor-protection-circuit-breaker-25a-3rv2031-4db10-eb12902385



Circuit breaker Cl.20 A release 18-25A - Motor protection circuit-breaker 25A 3RV2031-4DB10

Siemens

3RV2031-4DB10 4011209930445 EAN/GTIN

1240,03 CNY excl. VAT**

plus **shipping**



15-16 days* (CHN)

Circuit breaker CI.20 A release 18-25A 3RV2031-4DB10 overload release current setting 18 ... 25A, setting range of the instantaneous short-circuit release 325 ... 325A, with thermal protection, sensitive to phase failure, magnetic tripping technology, rated operational voltage 690 ... 690V, rated uninterrupted current lu 25A, rated operational power at AC-3, 230 V 5.5 kW, rated operational power at AC-3, 400 V 11 kW, connection type main circuit screw connection, design of the actuating element rotary knob, device design built-in device fixed installation technology, number of poles 3, rated limiting short-circuit breaking current lcu at 400 V, AC 65kA, protection class (IP) IP20, height 140mm, Width 55mm, depth 149mm, circuit breaker size S2 for motor protection, CLASS 20 A release 18...25 A N release 325 A screw connection standard switching capacity circuit breaker SIRIUS 3RV2 for motor protection for safe disconnection in the event of a short circuit and protection of consumers and system against overload, and for safe separation of the system from the network. The compact and small imafesten circuit breakers are optimized for use in consumer feeders due to their low waste heat, of course also for IE3/IE4 motors and equally for switching direct current. Worldwide approvals (e.g. IEC and UL/CSA) and use in potentially explosive applications (ATEX or IEC Ex) are a matter of course. Device variants are available for motor protection (also with overload relay function), system protection, short-circuit protection of starter combinations, transformer protection, as main and EMERGENCY STOP switches and for use in IT networks. They are available with a screw or spring-loaded connection for a fast, releases, signaling switches, etc., is the same for all sizes. The use of various power supply options, such as the associated SIRIUS 3RV29 infeed system, reduces the main circuit wiring considerably. The 3RV2 circuit breakers replace the tried-and-tested 3RV1 series. Simple, efficient, always up-to-date - the SIRIUS mod

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

