

https://www.eibabo.cn/siemens/circuit-breaker-c-0.5a-1-pole-230-400v-5sl6105-7-eb15705297



## Circuit breaker C 0.5A 1-pole 230/400V 5SL6105-7

×

## Siemens

5SL6105-7 4001869388106 EAN/GTIN

119,49 CNY excl. VAT\*\*

plus shipping



15-16 days\* (CHN)

Circuit breaker C0.5A 1-pole 6kA 5SL6105-7 tripping characteristic C, number of poles (total) 1, number of fused poles 1, rated current 0.5A, rated voltage 400V, rated switching capacity Icn to EN 60898 at 230 V 6kA, rated switching capacity Icn to EN 60898 at 400 V 6kA, rated switching capacity Icu according to IEC 60947-2 at 230 V 6kA, rated switching capacity Icu according to IEC 60947-2 at 400 V 6kA, type of voltage AC, frequency 50 ... 50Hz, energy limitation class 3, overvoltage category 3, degree of pollution 2, additional equipment possible, Width in pitch units 1, installation depth 70mm, degree of protection (IP) IP20, ambient temperature during operation -25 ... 45°C, connectable conductor cross-section, stranded 0.75 ... 25mm², connectable conductor cross-section, solid 0.75 ... 25mm², circuit breaker stranded 0.75 ... 25mm², connectable conductor cross-section, solid 0.75 ... 25mm², circuit breaker 50/400V 6kA, 1-pole, C, 0.5A The circuit breaker is the circuit breaker for short-circuit protection. The miniature circuit breakers from Siemens as an important part of the SENTRON protection components for the electrical installation offer effective personal and system protection through safe shutdown in the event of an overload or short circuit. Convenient assembly and connection technology, standard additional components and a consistent design - these are the hallmarks of the device family. Whether for infrastructure or for industrial requirements, Siemens offers miniature circuit breakers for all applications and every area of use. The Siemens miniature circuit breakers are characterized above all by: 1. Effective personal investment and system protection against overload and short circuits. 2. Uniform accessories in a wide variety, easy to assemble and exchangeable at any time. 3. Reliable safety during installation thanks to the grip and touch protection included as standard. 4. Tool-free removal from the top-hat rail or from the busbar assembly through convenient slide-hand operation. 5. Data ma

## YOUR ADVANTAGES



**WORLDWIDE TRADE**Corporate video eibmarkt®



COMPLAINTS HANDLING
Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



**25 YEARS OF EXPERIENCE** *In worldwide mail order* 



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



**DATA PROTECTION**Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- \*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

