

Item Number EB15705680

https://www.eibabo.cn/eltako/timer-2-channel-s2u12ddx-uc-eb15705680



Timer 2-channel S2U12DDX-UC

×

Eltako

S2U12DDX-UC 23200901 4010312603208 EAN/GTIN

378,94 CNY excl. VAT**

plus shipping



4-5 days* (CHN)

Time switch 2-channel 16A 250VAC 1+1S S2U12DDX-UC type of mounting DIN rail, number of channels 2, supply voltage 8 ... 230V, type of supply voltage AC/DC, frequency of supply voltage 50 ... 50Hz, power reserve in hours 480, Text guidance in the display, 24-hour program, weekly program, astro program, random program, quartz-controlled, contact design make contact, shortest switching time channel 1 1min, shortest switching time channel 2 1min, number of memory slots 60, automatic summer/winter time changeover, manual operation, external button input, rated switching current at 250 V AC 16A, potential-free switching contact, degree of protection (IP) IP20, width in modular units 1, width 18mm, height 82mm, depth 58mm, 2-channel time switch. 1+1 NO potential-free eswitching contact, degree of protection (IP) IP20, width in modular units 1, width 18mm, height 82mm, depth 58mm, 2-channel time switch. 1+1 NO potential-free eswitching contact, degree of protection (IP) IP20, width in modular units 1, width 18mm, height 82mm, depth 58mm, 2-channel time switch. 1+1 NO potential-free eswitching contact, degree of protection (IP) IP20, width in modular units 1, width 18mm, height 82mm, depth 58mm, 2-channel time switch. 1+1 NO potential-free eswitching eswitching 10N-EN 60715 TH35. 1 pitch unit = 18mm wide, 58mm deep. With the patented Eltako duplex technology (DX), the normally potential-free contacts can still switch at zero crossing when switching 230V AC voltage 50Hz and thus drastically reduce wear. Simply connect the N conductor to terminal (N) and L to 1(L) and/or 3(L). This results in an additional standby loss of just 0.1 watts. Due to the use of bistable relays, there is no coil power loss and no heating as a result, even when switched on. Up to 60 timer memory locations are freely distributed among the channels. With date and automatic summer/winter time changeover. Power reserve without battery approx. 7 days. Each memory location can either be occupied with the astro function (automatic switching after sunris

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING
Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE *In worldwide mail order*



REFUNDWithin 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

