

**LED ceiling/wall light 3000K D500 H100 - Ceiling-/wall luminaire 1x21W 211398.002**



**RZB**

211398.002

4051859066408 EAN/GTIN

**1799,60 CNY** excl. VAT\*\*

plus shipping



15-16 days\* (CHN)

LED ceiling/wall light 3000K D500 H100 211398.002 Energy efficiency class of the exchangeable lamp supplied A+, Highest energy efficiency class of the exchangeable lamp A+, Lowest energy efficiency class of the exchangeable lamp A+, Energy efficiency class spectrum A++ to E, Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, Light source LED not interchangeable, With light source, Suitable for VDU workstations according to EN 12464-1, Suitable for number of light sources 1, Other socket, Material of the housing plastic, Housing color white, Material of the cover glass opal, Design of the grid without, Type of voltage AC, rated voltage 220 ... 240V, control gear not required, without dimming function, light distributor without, symmetrical light distribution, beam angle unshielded/diffuse, light emission direct/indirect, rated service life L70/B10 at 25 °C 50000h, protection class (IP) IP43, impact resistance IK03, protection class I, rated Ambient temperature according to IEC62722-2-1 25 ... 25°C, glow wire test according to IEC 60695-2-11 960 °C - 30 s, suitable for lamp power 21 ... 21W, max. system power 21W, rated luminous flux according to IEC 62722-2 -1 2100lm, light color white, color temperature 3000 ... 3000K, color rendering index CRI 80-89, luminous efficacy of luminaire 100lm/W, height/depth 100mm, outer diameter 500mm, type of wiring termination, number of poles 3, conductor cross-section 2.5mm², connection type plug-in terminal, mouth-blown Three-layer opal glass (triplex glass) satin matt. The triplex glass ensures particularly homogeneous, soft and glare-free light. In numerous diameters from 250 to 630 mm. Flat design. Glass attachment with spring system or bayonet lock. Light color 830. Plastic holder. The cover is fastened with a bayonet catch. Cover Glass opal, satin finish, hand-blown. IP43 ceiling mounting, IP44 wall mounting.

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

