

## Item Number EB11596761

https://www.eibabo.cn/zumtobel/led-recessed-ceiling-light-r100h-18w840230valwh-downlight-spot-floo dlight-panos-evo-60815169-eb11596761



## LED recessed ceiling light R100H 18W840230VALWH - Downlight/spot/floodlight PANOS EVO #60815169

×

## Zumtobel

PANOS EVO #60815169 60815169 4053167130529 EAN/GTIN

1268,97 CNY excl. VAT\*\*

plus shipping



15-16 days\* (CHN)



LED recessed ceiling light R100H 18W840230VALWH PANOS EVO 60815169 Suitable for recessed mounting, Suitable for ceiling mounting, Adjustability not adjustable, Light source LED cannot be replaced, With light source, Suitable for number of light sources 1, Socket without, Housing material aluminium, Housing color white, Cover material opal plastic, Voltage type AC, Nominal voltage 220 ... 240V, LED nominal current at constant current 82 ... 82mA, Control gear LED control gear, current-controlled, With control gear, Without dimming function, Reflector without, Light distribution symmetrical, Light emission direct, Rated service life L70/B50 at 25° C 100000h, rated service life L90/B50 at 25° C 33000h, degree of protection (IP) IP20, impact resistance IK04, protection class II, max. system power 18W, light color white, color temperature 4000 ... 4000K, Color rendering index CRI 80-89, rated luminous flux according to IEC 62722-2-1 1613lm, power factor 0.95, height/depth 123mm, ext diameter 113mm, installation height/depth 140mm, installation diameter 100mm, suitable for VDU workstations according to EN 12464-1, glow wire test according to IEC 60695-2-11 850°C - 30 s, color consistency (McAdam ellipse) SDCM3, LED recessed ceiling light (complete light), "Stable White", cut-off angle 45°, fitted with: 18 W LED840, color rendering Ra > 80, color temperature 4000 K (neutral white), color location tolerance (initial MacAdam): 3, luminous flux of luminaires: 1613 lm, luminous efficacy of luminaires: 90 lm/ W, service life: 50000h at 85% luminous flux, with ballast unit, modular, high-quality optical unit consisting of reflector and LED light chamber, integrated in the optimized heat management system made of die-cast aluminium, smooth reflector aluminium-sputtered, highly specular, iridescence-free, reflector/cover ring made of high-quality, UV Resistant polycarbonate (PC), white cover ring, mounting ring made of glass-fibre reinforced polycarbonate (PC), grey, tool-free quick assembly of the luminaire unit using a bayo

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



**DATA PROTECTION**Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- \*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

