

Item Number EB15706719

https://www.eibabo.cn/schneider-electric/circuit-breaker-3-pole-32a-b-ic60n-miniature-circuit-breaker-3p-b32a-a9f03332-eb15706719



Circuit breaker, 3-pole, 32A B IC60N - Miniature circuit breaker 3-p B32A A9F03332

×

Schneider Electric

A9F03332 3606480439957 EAN/GTIN

208,08 CNY excl. VAT**

plus **shipping**



4-5 days* (CHN)

Circuit breaker 3P 32A B IC60N A9F03332 tripping characteristic B, number of poles (total) 3, number of fused poles 3, rated current 32A, rated voltage 400V, rated insulation voltage Ui 500V, rated impulse withstand voltage Uimp 6kV, rated switching capacity Icn according to EN 60898 at 230 V 6kA, rated switching capacity Icn according to EN 60898 at 400 V 6kA, rated switching capacity Icu according to IEC 60947-2 at 230 V 20kA, rated switching capacity Icu according to IEC 60947-2 at 400 V 10kA, type of voltage AC/DC, frequency 50 ... 60Hz, energy limitation class 3, overvoltage category 4, degree of pollution 3, additional equipment possible, width in module widths 3, installation depth 44.5mm, degree of protection (IP) IP20, ambient temperature during operation 35 ... 70°C, connectable conductor cross-section stranded 1 ... 25mm², connectable conductor cross-section solid 1 ... 35mm², Circuit breaker Acti 9 iC60N, 6kA (IEC/EN 60898-1), 10kA (IEC/EN 60947-2). 3-pole, rated current 32A, B characteristic, operating voltage (Ue) 380-415V AC, insulation voltage (Ui) 500V AC. Double connection terminal for cable and pin comb rail on the top and bottom of the device. Snap action for low-wear switching of the contacts. On-board insulation cover. Actuation of the DIN rail fastening element on the front of the device for tool-free assembly and easy access for the user. With mechanical error message display on the front (VisiTrip) for displaying trips due to overload or short circuit. Safe contact indicator (VisiSafe) of the miniature circuit breaker, green indicator means there is no voltage on the outgoing side. Terminals IP20, moving insulation cover. Double connection terminal from above or below. Simple removal of the individual device with the phase busbar installed, thanks to the fastening element that can be reached from the front. Technology of trip unit - thermomagnetic. Can be combined with the FI circuit breakers of the Acti 9 iID series and the FI block Vigi iC60. Additional add-on auxiliary modules (optio

YOUR ADVANTAGES



WORLDWIDE TRADE Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE

Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

