


**Circuit breaker ICU=25kA, IN=100A, 3p.  
3VA1110-3EE36-0BF0**


**Siemens**  
3VA1110-3EE36-0BF0  
4042949321064 EAN/GTIN

**3268,57 CNY** excl. VAT\*\*  
plus shipping



15-16 days\* (CHN)

Circuit breaker ICU=25kA, IN=100A, 3p. 3VA1110-3EE36-0BF0 Rated uninterrupted current  $I_n$  32A, rated voltage 690 ... 690V, rated limiting short-circuit breaking current  $I_{cu}$  at 400 V, 50 Hz 55kA, overload release current setting 22 ... 32A, setting range of the instantaneous short-circuit release 320 ... 320A, connection type main circuit box terminal, device type built-in device Permanent installation, Suitable for top-hat rail mounting, Top-hat rail mounting optional, Number of auxiliary contacts as NC contacts 0, Number of auxiliary contacts as NO contacts 0, Number of auxiliary contacts as changeover contacts 2, With tripped indicator, With undervoltage release, Number of poles 3, Position of the connection for the main circuit at the front, Design of the actuating element toggle lever, complete device with protection unit, optional motor drive, degree of protection (IP) IP40, circuit breaker 3VA1 IEC Frame 160 switching capacity class N  $I_{cu}$ =25kA @ 415V 3-pole, system protection TM220, ATFM,  $I_n$ =100A overload protection  $I_r$ =70A...100A short-circuit protection  $I_i$ =10 x  $I_n$  In terminal connection undervoltage release (UVR) 24V DC 1 auxiliary switch HQ 1 tripped signaling switch HQ 3VA1 molded case circuit breaker for system protection. The 3VA molded case circuit breakers from Siemens, as an important part of the SENTRON protective components for industrial applications and for applications in the infrastructure sector, offer effective starter and motor protection for systems through safe shutdown in the event of overload and short circuits. The 3VA molded case circuit breakers set standards in terms of flexibility and modular variety of accessories. Uniform accessories for several sizes across all series of 3VA1 and 3VA2 molded case circuit breakers. This variant of the 3VA molded case circuit breaker is primarily characterized by: 1. Compact design. 2. Available as a variant for system protection 3. Depending on the size: 1 to 4-pole versions. 4. Depending on size: Switching capacity of 16 kA ... 70 kA at 415 V for 3 or 4-pole switches and 36 kA at 240 V for 1-pole switches. 5. Installation in fixed installation and plug-in technology possible. 6. The series has a thermal-magnetic overcurrent release. 7. Suitable for both AC and DC application. 8. Modular and easy to assemble internal accessories with multiple functions. 9. Consistent accessory platform for all 3VA molded case circuit breakers. For the safe, efficient electrical infrastructure in buildings and industry, Siemens offers an integrated portfolio of protective switching, measuring and monitoring devices, distribution systems, switches and...

**YOUR ADVANTAGES**


**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler at a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

