



Load-break switch 32A, 3-pole, size 1 - Safety switch 3-p 15kW 3KD2232-2ME10-0



Siemens
3KD2232-2ME10-0
4001869471754 EAN/GTIN

530,95 CNY excl. VAT**
plus shipping



15-16 days* (CHN)

Load-break switch 32A, 3-pole, size 1 3KD2232-2ME10-0 Design as main switch Design as maintenance/repair switch Design as safety switch Number of switches 1 Max. rated operational voltage Ue at AC 1000V Rated uninterrupted current Iu 32A Rated uninterrupted current at AC 23, 400 V 32A, rated continuous current at AC-21, 400 V 32A, rated short-time withstand current Icw 3kA, rated operational power at AC-23, 400 V 15kW, switching capacity at 400 V 15kW, number of poles 3, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as changeover contact 4, device design built-in device, suitable for distributor installation, suitable for intermediate installation, color of the operating element grey, design of the operating element long turning handle, lockable, connection type main circuit box terminal, protection class (IP), front side IP20, protection class (NEMA) other, switch-disconnector 32A, size 1, 3-pole front drive on the left Complete device with direct drive, gray box terminal Switch disconnector 3KD up to 1600 A as a powerful main EMERGENCY STOP or repair switch. 3KD switch-disconnectors up to 1600 A from Siemens offer reliable personal protection and ensure high system availability in industry, infrastructure and buildings. As the main EMERGENCY STOP or repair switch, 3KD switch disconnectors reliably switch electrical equipment under load and offer a safety disconnection function and distance in low-voltage circuits. 1. Reliable protection against electrical accidents. 2. Robust technology for high system availability. 3. Versatile in use with variable connection and drive types. 4. Easy retrofitting of additional functions with a wide range of accessories. 5. Fast mounting on the DIN rail for sizes up to 200 A. 6. Efficient engineering thanks to extensive CAX data. 7. Uncomplicated documentation with the manual configurator. 8. Suitable for wind power and solar power systems. For the safe, efficient electrical infrastructure in buildings and industry, Siemens offers an integrated portfolio of protective switching, measuring and monitoring devices, distribution systems, switches and socket outlets.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler at a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

