

Item Number EB13902419

https://www.eibabo.cn/zumtobel/led-downlight-r150l16wled830ldofal-downlight-spot-floodlight-panos-e vo-60816026-eb13902419



LED downlight R150L16WLED830LDOFAL - Downlight/spot/floodlight PANOS EVO #60816026



Zumtobel

PANOS EVO #60816026 60816026 4053167208099 EAN/GTIN

1302,46 CNY excl. VAT**

plus shipping



15-16 days* (CHN)



LED downlight R150L16WLED830LDOFAL PANOS EVO 60816026 Suitable for recessed mounting, Suitable for ceiling mounting, Adjustability not adjustable, Lamp LED cannot be replaced, With lamp, Suitable for number of lamps 1, Socket without, Housing material aluminium, Housing color white, Cover material opal plastic, Type of voltage AC, nominal voltage 220 ... 240V, nominal LED current at constant current 74 ... 74mA, control gear current-controlled LED control gear, with control gear, DALI dimming, reflector without, symmetrical light distribution, direct light emission, rated service life L70/B50 at 25 °C 100000h, rated service life L80/B50 at 25 °C 66000h, rated service life L90/B50 at 25 °C 33000h, degree of protection (IP) IP20, impact resistance IK04, protection class II, max. system power 16W, light color white, color white, color white, color rendering index CRI 80-89, rated luminous flux according to IEC 62722-2-1 1846lm, power factor 0.94, height/depth 84mm, outer diameter 168mm, installation height/depth 81mm, installation diameter 150mm, glow wire test according to IEC 60695-2-11 850 °C - 30 s, color consistency (McAdam ellipse) SDCM3, LED recessed ceiling light (complete light), use in limited space in the ceiling: installation depth 80, color temperature 3000 K (warm white), color location tolerance (initially MacAdam): 3 lights Luminous flux: 1846 lm, luminaire luminous efficacy: 115 lm/W, service life: 50000h at 85% luminous flux, with separate ballast unit DALI controllable luminaire (DALI only), high-quality reflector unit locked to modular LED light chamber via bayonet lock, highly efficient LED light chamber integrated in optimised, passive heat management made of die-cast aluminium, reflector: faceted, aluminised, highly specular, iridescence-free, reflector/cover ring a unit made of high-quality, UV-resistant polycarbonate (PC), white cover ring, mounting ring made of glass-fibre reinforced polycarbonate (PC), grey, tool-free quick assembly of the lamp unit using a bayonet catch, IP44_IP20, lamp

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE
In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

