



Load-break switch 400A, 3-pole, size 3 - Safety switch 3-p 200kW 3KD4230-0PE10-0



Siemens
 3KD4230-0PE10-0
 4001869472881 EAN/GTIN

2396,98 CNY excl. VAT**
 plus shipping



15-16 days* (CHN)

Load-break switch 400A, 3-pole, size 3 3KD4230-0PE10-0 Design as a main switch Design as a maintenance/repair switch Design as a safety switch Design as an EMERGENCY STOP device Number of switches 1 Max. rated operating voltage Ue at AC 1000V Rated uninterrupted current Iu 400A, rated uninterrupted current at AC-23, 400 V 400A, rated uninterrupted current at AC-21, 400 V 400A, rated short-time withstand current Icw 13kA, rated operational power at AC-23, 400 V 200kW, switching capacity at 400 V 220kW, number of poles 3, number of auxiliary contacts as NC contact 6, number of auxiliary contacts as NO contact 6, number of auxiliary contacts as changeover contact 0, device design built-in device fixed installation technology, color of the actuating element other, design of the actuating element without, connection type main circuit flat plug connection, protection class (IP), front side IP00, protection class (NEMA) other, Switch disconnector 400A, size 3, 3-pole front operating mechanism on the left Basic device without handle Flat terminal 3KD switch disconnectors up to 1600 A as a powerful main EMERGENCY STOP or repair switch. 3KD switch-disconnectors up to 1600 A from Siemens offer reliable personal protection and ensure high system availability in industry, infrastructure and buildings. As the main EMERGENCY STOP or repair switch, 3KD switch disconnectors reliably switch electrical equipment under load and offer a safety disconnection function and distance in low-voltage circuits. 1. Reliable protection against electrical accidents. 2. Robust technology for high system availability. 3. Versatile in use with variable connection and drive types. 4. Easy retrofitting of additional functions with a wide range of accessories. 5. Fast mounting on the DIN rail for sizes up to 200 A. 6. Efficient engineering thanks to extensive CAX data. 7. Uncomplicated documentation with the manual configurator. 8. Suitable for wind power and solar power systems. For the safe, efficient electrical infrastructure in buildings and industry, Siemens offers an integrated portfolio of protective switching, measuring and monitoring devices, distribution systems, switches and socket outlets.

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

