

Item Number EB16400703

https://www.eibabo.cn/esylux/ceiling-presence-detector-eb-360-degrees-pd-c360-8-mini-slave-eb1640 0703



Ceiling presence detector EB, 360 degrees PD-C360/8 mini Slave

×

ESYLUX

PD-C360/8 mini Slave EP10426063 4015120426063 EAN/GTIN

564,88 CNY excl. VAT**

plus **shipping**



4-5 days* (CHN)

Ceiling presence detector EB, 360 degrees PD-C360/8 mini slave version presence detector, sensor type passive infrared, scanning angle 360°, optimum mounting height 3m, max. range to one side 4m, max. presence area 7.08m², max. frontal range 2m, Detection field diameter on floor 8m, with signal unit, suitable for ceiling mounting, mounting type flush-mounted, connection type other, material plastic, material quality thermoplastic, halogen-free, surface untreated, surface design matt, color other, transparent, protection class (IP) IP55, voltage type AC, nominal voltage 230V, min. switch-on time 0s, max. switch-on time 0min, switch-off delay 0s, switch-on delay 30s, horizontal detection angle 180 ... 360°, sensor swivel range, horizontal 0°, sensor swivel range, vertical 0°, temperature -25 ... 50°C, number of switching zones 0, height 60mm, diameter 33mm, installation depth 45mm, installation diameter 25mm, min. depth of the device box 45mm, slave presence detector to expand the detection range of a master presence detector with 360° detection range for ceiling mounting. Range of up to 8 m in diameter for cost-effective system expansion with up to 10 additional extensions. All parameters are set on the master detector, the slave detector detects movements and forwards them to the master. Small, compact size for an installation hole diameter of only 25 mm. Fixed connection cable with a length of 60 cm. New, universal ESYLUX clamping technology for quick installation in suspended ceilings, lights, flush-mounted sockets, cupboards, etc. Recessed ceiling installation in suspended, closed ceilings with the enclosed spring clips or clamping ring. Targeted blanking of areas using the enclosed lens mask. The slave detector can be connected to the following detectors:- PD-C360i/8 mini, PD-C360i/12 mini, PD-C360i/12 mini DIM, PD-C360i/12 mini DIM,

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®




COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

