
Item Number
EB12207425

28.03.2024/10:08

https://www.eibabo.cn/rzb/led-wall-light-4000k-w.bwm-ceiling-wall-luminaire-1x10w-621095.004.1.19-eb12207425



LED wall light 4000K w.BWM - Ceiling-/wall luminaire 1x10W 621095.004.1.19

RZB
621095.004.1.19
4051859260363 EAN/GTIN

2245,36 CNY excl. VAT**
plus **shipping**

15-16 days* (CHN)

LED wall light 4000K with BWM 621095.004.1.19 Suitable for wall mounting, Suitable for surface mounting, LED bulbs cannot be replaced, With bulbs, Suitable for computer workstations according to EN 12464-1, Suitable for number of bulbs 1, Other socket, Housing material aluminium, Housing color silver, Material of the cover plastic opal, design of the louvre without, type of voltage AC, nominal voltage 220 ... 240V, operating device not required, without dimming function, light distributor without, light distribution symmetrical, beam angle unshielded/diffuse, light emission direct/indirect, protection class (IP) IP54, protection class (NEMA) other, impact resistance IK02, protection class I, rated ambient temperature according to IEC62722-2-1 -20 ... 35°C, with motion detector, with light sensor, glow wire test according to IEC 60695-2-11 650 °C - 30 s, suitable for Lamp power 10 ... 10W, max. system power 10W, rated luminous flux according to IEC 62722-2-1 610lm, light color white, color temperature 4000 ... 4000K, Far b rendering index CRI 80-89, luminous efficacy of luminaire 61lm/W, width 130mm, height/depth 410mm, length 230mm, type of wiring termination, number of poles 3, conductor cross-section 2.5mm², connection type plug-in terminal, wall lights in classic design language. Opal glass for a glare-free appearance. Resistant plastic cylinders made of UV-stabilized polyethylene also allow use in an environment with increased mechanical loads. High-quality materials glass, aluminum and stainless steel for a long service life. Different equipment variants for optimal and energy-saving operation. Wall bracket in die-cast aluminium, powder-coated. Diffuser plastic (polyethylene) opal satin finish. The cover is fastened with a bayonet catch. Wall arm with motion detector including twilight switch. Mounting height of the wall light 2.0 m to 2.5 m. Maximum switching capacity 1000 W (resistive load), switch-on time adjustable from 6 seconds to 8 minutes, twilight value adjustable from 5 lux to 2000 lux, horizontal detection angle 360°, vertical 25°, detection range 9 m

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online