



Wireless actuator universal dimming Switch FUD61NPN-230V



Eltako
FUD61NPN-230V
 30100835
 4010312300299 EAN/GTIN

611,22 CNY excl. VAT**
 plus shipping



4-5 days* (CHN)

Wireless actuator universal dimmer switch FUD61NPN-230V Suitable for dimmers, in the housing, power supply 230 V AC, push-button operation, flush-mounted installation, material plastic, material quality thermoplastic, halogen-free, surface other, surface finish matt, type of attachment other, color blue, suitable for protection class (IP) IP20, radio frequency 868MHz, rolling code system, number of commands 32, universal dimmer switch, power MOSFET up to 300W. Automatic lamp detection. Standby loss only 0.7 watts. Minimum brightness or dimming speed adjustable. With children's room, snooze and light alarm switch. Additionally with light scene control. Encrypted radio, bidirectional radio and repeater function can be switched on. For flush mounting. 45mm long, 45mm wide, 33mm deep. Universal dimmer switch for lamps up to 300W, depending on the ventilation conditions. Dimmable energy-saving lamps ESL and dimmable 230V LED lamps also depend on the lamp electronics. Switching at zero crossing with soft on and soft off to protect the lamp. Supply, switching and control voltage locally 230V. No minimum load required. The set brightness level is saved when the device is switched off (memory). In the event of a power failure, the switching position and the brightness level are saved and, if necessary, switched on when the supply voltage returns. Automatic electronic overload protection and over-temperature shutdown. Encrypted sensors can be taught in. Bidirectional radio and/or a repeater function can be switched on. Each status change and received central control telegrams are then confirmed with a radio telegram. This radio telegram can be taught into other actuators such as the FSR61NP-230V, the GFVS software and universal displays. The current dimming value is also displayed in % in the GFVS software. With the upper %lamp/dim speed rotary switch, either the minimum brightness (fully dimmed down) or the dimming speed can be set. During operation, the lower rotary switch determines whether the automatic lamp recognition should take effect or special comfort positions. The LED accompanies the learning process according to the operating instructions and indicates radio control commands during operation by flashing briefly.

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

