Item Number
EB12207152

29.03.2024/10:16

https://www.eibabo.cn/rzb/led-wall-ceiling-light-2700-6500k-ceiling-wall-luminaire-1x33w-312269.004.2.730-eb12207152



LED wall ceiling light 2700-6500K - Ceiling-/wall luminaire 1x33W 312269.004.2.730

RZB
312269.004.2.730
4051859269540 EAN/GTIN

4802,47 CNY excl. VAT**

plus **shipping bulky item**

15-16 days* (CHN)

LED wall-ceiling light 2700-6500K 312269.004.2.730 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, LED bulbs cannot be replaced, With bulbs, Suitable for computer workstations according to EN 12464-1, Suitable for number of bulbs 1, Other socket, Housing material aluminium , Housing color aluminium, Cover material structured plastic, Design of the louvre without, Voltage type AC, Nominal voltage 220 ... 240V, Control gear LED control gear, current-controlled, With control gear, Manufacturer-specific dimming, Dimming dependent on the control gear, Light distributor without, Light distribution symmetrical, Beam angle unshielded /diffuse, light emission direct, rated service life L70/B10 at 25 °C 50000h, degree of protection (IP) IP40, degree of protection (NEMA) other, impact resistance IK03, protection class I, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, glow wire test according to IEC 60695-2-11 650 °C - 30 s, suitable for lamp power 33 ... 33 W, max. system power 28W, rated luminous flux according to IEC 62722-2-1 3350lm, light color multicolored, color temperature 2700 ... 6500K, color rendering index CRI 80-89, luminous efficacy of luminaire 120lm/W, power factor 0.98, width 298mm, height/depth 49mm , length 1198mm, type of wiring termination, number of poles 3, conductor cross-section 1.5mm², connection type plug-in terminal, highly aesthetic series of lights with extremely flat overall height and progressive LED technology. RZBSIDELITE® technology: Lateral light coupling for above-average homogeneous luminance distribution. LED service life 50,000 h (L70, B10). Glare rating UGR: 19.0. Light guide and plastic cover made of non-yellowing PMMA. Infinitely height-adjustable 2-point steel wire suspension. Very simple installation thanks to Plug & Play connection system.

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

COMPLAINTS HANDLING
Obliging and 100% safely

SHORT DELIVERY TIME
Warehousing

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

25 YEARS OF EXPERIENCE
In worldwide mail order

REFUND
Within 14 days

DHL TRACK & TRACE
Shipment tracking

ORDER LIVE CHAT
With order history

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online