

Item Number EB12207314

×

https://www.eibabo.cn/rzb/led-wall-ceiling-light-4000k-ceiling-wall-luminaire-1x10w-582005.002-eb122 07314



LED wall ceiling light 4000K - Ceiling-/wall luminaire 1x10W 582005.002

RZB 582005.002 4051859217480 EAN/GTIN

854,95 CNY excl. VAT**

plus **shipping**

I5-16 days* (CHN)

Ceiling-/wall luminaire 1x10W, Suitable for wall mounting yes, Suitable for pendulum suspension no, Suitable for ceiling mounting yes, Suitable for recessed mounting no, Suitable for surface mounting yes, Illuminant LED not interchangeable, With illuminants yes, Suitable for light band configuration no, Suitable for number of lamps 1, Lamp holder other, Material of the housing Aluminum, Housing color white, Material of the cover Plastic opal, Type of grid without, Voltage AC, Rated voltage 220..240 V, Operating device not mandatory, With operating device no, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming Potentiometer (device-integrated) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Dimming dependent on control gear no, Without dimming function yes, light distributor without, Light distribution symmetrical, Beam angle free radiate/diffuse, Light outlet directly, Rated service life L70/B50 at 25 °C 45,000 h, Degree of protection (IP) IP66, Protection class (NEMA) other, Impact resistance IK10, Protection class I, Suitable for emergency light no, With motion detector no, With light sensor no, With louvers no, Suitable for lamp power 10W, Max. System performance 10W, Rated luminous flux according to IEC 62722-2-1 390 Im, Light color white, Color temperature 4000K, Color rendering index CRI 80-89, luminous efficacy 39 Im/W, Height/depth 70 mm, Outer diameter 268 mm, Type of wiring graduation, Number of poles 3, Conductor cross-section 2.5 mm², Connection type Plug-in terminal

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

