



Wall light E27 QA60/57W - Ceiling-/wall luminaire 1x57W 582011.004



RZB
582011.004
4051859217800 EAN/GTIN

744,46 CNY excl. VAT**
plus shipping



15-16 days* (CHN)

Wall light E27 QA60/57W 582011.004 Suitable for wall mounting, Suitable for surface mounting, Light source HV halogen lamp, Suitable for number of light sources 1, Socket E27, Housing material aluminium, Housing color silver, Cover material opal plastic, Grid design without, Type of voltage AC/DC, control gear not required, dimming mains voltage modulation, without dimming function, light distributor without, light distribution asymmetrical, beam angle unshielded/diffuse, light emission direct/indirect, protection class (IP) IP66, protection class (NEMA) other, impact resistance IK10, protection class I, rated ambient temperature according to IEC62722-2 -1 -20 ... -20°C, Suitable for emergency lighting, Glow wire test according to IEC 60695-2-11 850 °C - 30 s, Suitable for lamp power 57 ... 57W, Max. system power 57W, Power factor 1, Height/ Depth 96mm, outer diameter 268mm, type of wiring termination, number of poles 3, conductor cross-section 1.5mm², connection type plug-in terminal, LED: use smarter, more cost-effectively ger LED modules for mains voltage with high LED system light output for energy-saving operation. Bayonet catch with snap lock for an elegant appearance with no visible screws. Durability through the use of corrosion-resistant aluminium, glass or PC. Seawater resistant coating. Light color 840: the neutral white light source guarantees a brilliant appearance of the opal cover. Fastening points outside the lamp compartment, safe installation through consistent avoidance of errors. Bore tolerance compensation: Fastening in the slot - axes rotated 90°. The flat, circular design offers universal applicability. Free selection from 8 housing variants guarantees great freedom of design. Other equipment variants: As a house number light with an integrated twilight switch. Versions for escape route lighting with central battery feed. Housing made of corrosion-resistant die-cast aluminum for outdoor use, powder-coated. Half-shell cover with diffuser spherical cap made of opal plastic (polycarbonate) with mounting fixture. Screwless installation of the diffuser via bayonet catch with snap lock. Fastening outside the sealed area with bore tolerance compensation. Mains connection 2x 3x 1.5 mm². Energy efficiency class A, C, E1 A+

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

