



KNX presence detector Normal ws - KNX Movement sensor for home automation 6131/30-24-500



ABB
6131/30-24-500
2CKA006132A0346
4011395185926 EAN/GTIN

1001,37 CNY excl. VAT**
plus shipping

 **15-16 days*** (CHN)

KNX presence detector normal ws 6131/30-24-500 bus system KNX, other bus systems without, version presence detector, type of mounting surface-mounted, material plastic, material quality thermoplastic, surface untreated, design of the surface matt, color white, RAL number (similar) 9016, With bus connection, extension input, creep-under protection/rear field monitoring, stairwell monitoring, adjustable response brightness, teach function for response brightness, optimum installation height 3m, detection field diameter on the floor 12m, number of channels 2, min. switch-on time 10s, max. switch-on time 1092min, min. depth of the device box 0mm, detection range (at 2.5 m, 3 m and 4 m mounting height): circular. Seated people Ø: max. 8 m, max. 10 m and max. 14 m. Walking people Ø: max. 10 m, max. 12 m and max. 16 m. Structure height 23 mm. With 2 channels. For the targeted switching of light strips on and off depending on the brightness of the room. Regulation also possible depending on the movement. Use of the device as a presence and/or motion detector. Detector application with 2-stage switch-off function. Detector application with integrated monitoring function. Constant light switch with up to 2 independent channels. Constant light switch with max. 2 outputs for brightness-dependent switching of two light strips in the room. With integrated KNX bus coupler. Suitable for suspended ceilings with a panel thickness of 9 to 25 mm. Mounting hole dimension: Ø 68 mm. Suitable for surface mounting in combination with a AP housing. Does not fit in the British Standard and VDE flush-mounted box. Recommendation: HaloX-O flush-mounted box from Kaiser (item no. 1290-40) with the appropriate cover (1290-47 or 1290-85 for fair-faced concrete) or IBTronic H120-68 from Spelsberg (item no. 97600501).

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

