https://www.eibabo.cn/busch-jaeger/room-temperature-controller-10-fm-control-funct.-knx-room-thermostat-for-bus-system-sbr-u10.0.1-84-eb16519801

Room temperature controller 10-fm control funct. - KNX Room thermostat for bus system SBR/U10.0.1-84

Busch Jaeger
SBR/U10.0.1-84
2CKA006330A0008
4011395255179 EAN/GTIN

1806,67 CNY excl. VAT**

plus **shipping**

15-16 days* (CHN)

Room temperature controller 10-fm control funct. SBR/U10.0.1-84 KNX bus system, combination of control element, flush-mounted installation type, with theft/dismantling protection, with LED display, with display, plastic material, thermoplastic material quality, surface untreated, glossy surface design, color white, RAL number (similar) 9016, manual setpoint adjustment, presence button, parallel operation possible, protection class (IP) IP20, with bus connection, room temperature controller with 10-fold operating function, studio white, Busch installation bus KNX, ClimaECO sensors, room temperature controller with 10-fold heating/operating function Cooling mode/color concept Freely configurable multifunction control element. With integrated KNX bus coupler. With labeling field. Support of the KNX functions through an innovative color concept (yellow=lighting, blue=blinds, orange=RTR, magenta=scene and white=neutral/no function assignment) or standard red/green lighting. Button function: switching / dimming / blinds / send value / light scenes, etc. master/slave operation. With base load operation. The controller is a constant room temperature controller for fan convectors (fan coil) in 2- and 4-pipe systems and conventional heating or cooling systems The fan level can be switched manually or to automatic mode Temperature controller class: 1 Contribution to room heating energy efficiency: 1.0 %. Operating elements: Button contacts left/right Display elements: Display of the operating mode, temperature, fan coil level, humidity value, CO_2 value, time or date via LCD Connections: KNX line: Bus connection terminal Protection class device: IP 20 Temperature range device: -5 °C to 45 °C Dimensions (H x W x D): 166 mm x 90 mm x 13 mm

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online