



**LED street light 4000K - Luminaire for streets and places  
R2L2 S 48L #96275562**



**Zumtobel**  
R2L2 S 48L #96275562  
96275562  
3607640464253 EAN/GTIN

**5375,90 CNY** excl. VAT\*\*  
plus shipping

 **15-16 days\* (CHN)**

LED street light 4000K R2L2 S 48L 96275562 Light source LED not interchangeable, With light source, Suitable for number of light sources 1, Socket without, Housing material aluminium, Housing color gray, Cover material transparent glass, Type of voltage AC, Rated voltage 230 ... 230V, Control gear Current-controlled LED control gear, With control gear, Without dimming function, Energy efficiency class of the permanently installed lamp A++, A+, A (LED), Rated service life L70/B10 at 25 °C 100000h, Rated service life L70/B50 at 25 °C 100000h, Rated service life L80/B10 at 25 °C 100000h, Rated service life L80/B50 at 25 °C 100000h, Rated service life L90/B10 at 25 °C 100000h, Rated service life L90/B50 at 25 °C 100000h, Degree of protection (IP) IP66, Impact resistance IK08, Protection class II, Max. system power 101W, rated luminous flux according to IEC 62722-2-1 13720lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 70-79, power factor 0.95, width 362mm, height /Depth 155mm, Length 655mm, A LED Street Light, Mini, with 48 LEDs, powered at 700mA, Optics: Narrow Street. LED driver. Protection class II, IP66, IK08. Housing: Die-cast aluminum (EN AC-44300), powder-coated in THORN LIGHT GRAY, textured. Cover: glass, flat, tempered. Screws: stainless steel, with Ecolubric(R) treatment. Post-top mounting (diameter 60/76 mm, 0°/5°/10° tilt) or side-entry mounting (diameter 34/42/49/60 mm, 0°/-5°/-10°/-15° tilt). An additional adapter (59005840 R2L2 MA34/42 NPA) should be ordered for side-entry mounting to a diameter of 34/42 mm. Equipped with 50% power reduction circuit, activated 3 hours before and 5 hours after a calculated midnight. Can be disabled at installation with an easily accessible internal switch or cable clamp. Including LED module with 4000K. Dimensions: 655 x 362 x 155 mm Luminaire output: 101 W Luminaire luminous flux: 14898 lm Luminaire efficacy: 148 lm/W Weight: 12 kg Windage area: 0.05 m²

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

