

Item Number EB12507170

https://www.eibabo.cn/ridi-leuchten/led-lamp-l-tube-4000k-550mm-gen.-f-led-lamp-multi-led-b22d-white -l-tube055-0205409gf-eb12507170

LED Lamp L-TUBE 4000K 550mm Gen. F - LED-lamp/Multi-LED B22d white L-TUBE055 #0205409GF





Ridi-Leuchten

L-TUBE055 #0205409GF 0205409GF 4029299480290 EAN/GTIN

337,43 CNY excl. VAT**

plus shipping bulky item



15-16 days* (CHN)

LED lamp L-TUBE 4000K 550mm Gen. F L-TUBE055 0205409GF Energy efficiency class A++, energy efficiency class range A++ to E, nominal current 560 ... 560mA, lamp power 13 ... 13W, type of voltage DC, luminous flux 2000 ... 2000lm, rated luminous flux according to IEC 62722-2-1 2000lm, color rendering index CRI 80-89, lamp shape tube, double base, version glass/frosted cover, light color according to EN 12464-1 neutral white 3300 to 5300 K, base B22d, color white, light color 840 ... 840, color temperature 4000 ... 4000K, housing color white, color consistency (McAdam ellipse) SDCM3, dimmable, length 550mm, protection class (IP) IP20, weighted energy consumption in 1,000 hours 15kWh, average nominal service life 50000h, LED illuminant RIDI L-TUBE, Color rendering Ra >= 80, color location tolerance < 3 Step Mac Adam (initial). LED modules designed as a linear circuit board. Mid-power LEDs for even illumination and maximum efficiency. Basic profile made of extruded solid aluminum for optimal thermal management. Linear plate twisted continuously over the entire length with the basic profile. Cover made of clear, frosted or opal PMMA for efficient light emission, end cover made of robust PC, colour-coordinated with the cover. Operation with an external LED driver (to be ordered separately or installed in the light), constant current, safety extra-low voltage less than 60 volts (SELV-compliant). L-TUBE packed. Length 550 mm, power consumption 13 watts. Color rendering Ra > 80. Light color 3000 (...830...), 4000 (..840...) or 6500 Kelvin (...865...). Installation: Factory installation in many lights from the RIDI range. Tool-free, mechanical bulb replacement of the L-TUBE by actuating the spring steel clip and electrically via the socket-plug system.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®




COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

