

Item Number EB14201571

https://www.eibabo.cn/vaillant/pressure-resistant-hot-water-tank-boiler-electric-veh-100-8-exclusive-eb 14201571



Pressure-resistant hot water tank - Boiler electric VEH 100/8 exclusive

Vaillant

VEH 100/8 exclusive 0010019876 4024074789377 EAN/GTIN



5188,02 CNY excl. VAT**

plus shipping bulky item



4-5 days* (CHN)

Pressure-resistant hot water tank VEH 100/8 exclusive, energy efficiency class C, energy efficiency class spectrum A to G, boiler material steel, jacket material steel, volume of the tank 100l, nominal output 6kW, connection voltage 230 ... 400V, three-phase version, frequency 50 Hz, hanging version, With off-peak mode, can be used with normal water pressure, connection to a hot water pipe, warm-up time from 10 °C - 65 °C 55 min, tapping capacity at 60 °C, continuous operation 20 l/min, vertical placement, with temperature display, temperature limitation, max. permissible operating pressure 6 bar, with cleaning opening , protective anode, height 1082mm, width 504mm, depth 450mm, diameter 504mm, connection cold drinking water external thread, nominal inside diameter cold drinking water 1/2 inch (15), connection hot water external thread, nominal inside diameter hot water connection 1/2 inch (15), protection class (IP) IP25 , tapping profile L, VEH 100/8 exclusive wall-mounted electric water heater Product advantages - Minimum ready loss of thermal energy through highly efficient thermal insulation - rapid heating for additional hot water requirements - anti-scald protection that can be activated - anti-freeze function - connected load can be adjusted by moving jumpers Equipment - universal heating flange for single-circuit, dual-circuit and boiler operation - temperature controller infinitely adjustable from 7 to 85 degrees C - high-quality storage enamel and stainless steel heating elements with a long service life - IP25 jet water protection enables unrestricted installation in protection area I - Service-friendly thanks to the integrated ball valve for quick emptying Nominal capacity 100 I Permissible operating pressure 6 bar Standby heat loss 1.01/kW/24h Mixed water volume of 40 degrees C 196 I cold/warm water connection R 1/2 height/width / depth 1082/504/450 mm Weight (filled) 160 kg Weight (unpacked) 60 kg water heating

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION *Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

