

Sheathed cable shielded (N)YMStJ3x1,5/1,5Eca**Diverse**

(N)YMStJ3x1,5/1,5Eca

(N)YMStJ3x 1,5/1,5Eca R 50

**615,99 CNY** excl. VAT**

plus shipping



4-5 days* (CHN)

(N)YMStJ3x 1.5/1.5Eca R 50 sheathed cable, shielded conductor material copper, nominal conductor cross-section 1.5mm², conductor class class 1 = solid, number of cores 3, core insulation material polyvinyl chloride (PVC), core -Identification color, core color different, protective conductor, screen, drain wire, protective sleeve without, reinforcement/armouring without, jacket material polyvinyl chloride (PVC), jacket color gray, fire behavior class according to EN 13501-6 Eca, flame-retardant no, insulation integrity no, outer diameter approx 9.2mm, Perm. Outside cable temperature during assembly/handling -5 ... 70°C, perm. External cable temperature after assembly without vibration -40 ... 70°C, nominal voltage U0 300V, min. permissible bending radius, stationary use/permanently installed 37mm, nominal voltage U 500V, based on VDE 0250. With static screen to limit electromagnetic interference fields. This shielding is used when installing in the computer area, in hospitals or industrial control rooms with measuring devices that are particularly susceptible to interference. Suitable for installation in the living area of radiation-sensitive and particularly sensitive people. Laying on, in and under plaster in dry and damp rooms as well as in concrete and masonry, but not for direct embedding in vibrated or stamped concrete. Outdoor routing is only possible if the cable is not exposed to direct sunlight or if it is routed in cable ducts. Use in hazardous areas is not permitted. PVC outer sheath, core color code according to VDE 0293. Max. operating temperature 70 °C. Copper base: EUR 150 per 100 kg

YOUR ADVANTAGES**WORLDWIDE TRADE**

Corporate video eibmarkt®

**99% CUSTOMER SATISFACTION**

> 500,000 customers worldwide

**DHL TRACK & TRACE**

Shipment tracking

**COMPLAINTS HANDLING**

Obliging and 100% safely

**25 YEARS OF EXPERIENCE**

In worldwide mail order

**ORDER LIVE CHAT**

With order history

**SHORT DELIVERY TIME**

Warehousing

**REFUND**

Within 14 days

**DATA PROTECTION**

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

