


Storage - Boiler electric SH 50 S

Stiebel Eltron

SH 50 S

073048

4017210730487 EAN/GTIN

6316,63 CNY excl. VAT**

plus shipping bulky item



15-16 days* (CHN)

SH 50 S storage tank Energy efficiency class C, energy efficiency class spectrum A to G, boiler material steel, jacket material steel, volume of the tank 50l, nominal output 6kW, connection voltage 230... 400V, three-phase version, frequency 50 Hz, hanging version, applicable with normal Water pressure, warm-up time from 10 °C - 65 °C 30 min, tapping capacity at 60 °C, continuous operation 18l/min, wall installation, vertical placement, temperature limitation, max. permissible operating pressure 6bar, protective anode, height 740mm, width 510mm, depth 510mm, cold connection Drinking water external thread, nominal inside diameter of cold drinking water 1/2 inch (15), pipe outside diameter of cold drinking water 21.5 mm, connection of hot water outside thread, nominal inside diameter of hot water connection 1/2 inch (15), pipe outside diameter of hot drinking water 21.5 mm, protection class (IP) IP25, energy efficiency of hot water 38%, tap profile M, hot water wall storage tank for any desired hot water supply. -Closed (pressure-resistant) to supply several tapping points. Installation also in connection with plastic pipe systems (observe manufacturer's information and application limits). -Open (non-pressurized) to supply a tapping point. Electronic heat content indication with LED display in the control panel. Steel inner container with special direct enamel "anticor" and equipped as standard with signal anode (anti-corrosion rod) and indicator light in the control panel. Thermal insulation with minimal heat loss. Universal flange single-circuit operation. The water content is kept at the set temperature depending on the controller. Infinitely variable temperature setting from approx. 35 degrees C to approx. 82 degrees C or temperature limitation on the selector button. Automatic frost protection, signal lamp when heating up, exchangeable copper heating flange, radiator connections through complete. flange connector. Performance variants possible. Drain valve with hose connection G 3/4. Mounting aid with recessed grips. Pre-assembled suspension rail also allows mounting in the corner. Installation with: Safety group KV 30 or KV 40 with a pressure-resistant connection or fitting for open devices with a non-pressurized connection. Quality and safety marks: VDE/GS mark, radio protection mark, IP 25 D (jet water protected)

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

