Item Number
EB16215804

29.03.2024/09:07

https://www.eibabo.cn/siemens/sirius-compact-starter-ac-dc-110-240-v-reversing-starter-combination-0-09kw-3ra6250-1ap33-eb16215804



SIRIUS compact starter AC/DC 110-240 V - Reversing starter combination 0,09kW 3RA6250-1AP33

Siemens
3RA6250-1AP33
4011209715110 EAN/GTIN

4852,45 CNY excl. VAT**

plus **shipping**

15-16 days* (CHN)

SIRIUS compact starter AC/DC 110-240 V 3RA6250-1AP33 Type of motor starter Reversing starter, With short-circuit release, Rated control supply voltage Us at AC 50 Hz 110 ... 240 V, Rated control supply voltage Us at AC 60 Hz 110 ... 240 V, Rated control supply voltage Us at DC 110 . .. 240V, type of voltage for actuation AC/DC, rated operational power at AC-3, 400 V 0.09kW, rated operational current Ie 0.4A, overload release current setting 0.1 ... 0.4A, number of auxiliary contacts as NO contact 2, number of Auxiliary contacts as NC contacts 0, ambient temperature, upper limit without restrictions 40°C, tripping class adjustable, connection type main circuit other, design of electrical connection for auxiliary and control circuit screw connection, type of coordination according to IEC 60947-4-3 class 2, number of indicator lights 3, protection class (IP) IP20, degree of protection (NEMA) other, width 90mm, height 170mm, depth 165mm, SIRIUS compact starter reversing starter 690 V AC/DC 110...240 V 50...60 Hz 0.1...0.4 A IP20 connection Main circuit: pluggable, without terminals Control circuit connection: screw connection SIRIUS 3RA62 compact starter for direct starting of standard three-phase motors up to 32 A. The devices combine the functions of circuit breakers, contactors and electronic overload relays and have a very high level of operational reliability. A small variance simplifies the logistics. The compact design saves space in the control cabinet. Thanks to detachable clamps, easy replacement is possible. The devices are approved worldwide (eg IEC and UL/CSA). The compact starters are available as direct or reversing starters and are available with different setting ranges. Designed for AC/DC operation, they are available with screw-type spring-type terminals or without terminals. In addition to the communication connection via AS-Interface, the 3RA68 infeed system and auxiliary contacts and terminals are available as accessories. Simple, efficient, always up-to-date - the SIRIUS modular system .

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online