

Item Number EB16215835

https://www.eibabo.cn/siemens/sirius-compact-starter-ac-dc-110-240-v-reversing-starter-combination-1 5kw-3ra6250-1ep32-eb16215835



SIRIUS compact starter AC/DC 110-240 V - Reversing starter combination 15kW 3RA6250-1EP32

×

Siemens

3RA6250-1EP32 4011209715936 EAN/GTIN

7537,40 CNY excl. VAT**

plus **shipping**



15-16 days* (CHN)

SIRIUS compact starter AC/DC 110-240 V 3RA6250-1EP32 Type of motor starter Reversing starter, With short-circuit release, Rated control supply voltage Us at AC 50 Hz 110 ... 240 V, Rated control supply voltage Us at AC 60 Hz 110 ... 240 V, Rated control supply voltage Us at DC 110 ... 240V, type of voltage for actuation AC/DC, rated operational power at AC-3, 230 V, 3-phase 7500kW, rated operational power at AC-3, 400 V 15kW, rated operational current le 32A, overload release current setting 8 ... 32A, number of auxiliary contacts as NO contact 2, number of auxiliary contacts as NC contact 0, ambient temperature, upper limit without restrictions 40°C, tripping class adjustable, connection type main circuit screw connection, design of electrical connection for auxiliary and control circuit screw connection, type of coordination according to IEC 60947-4-3 class 2, number of Indicator light 3, degree of protection (IP) IP20, degree of protection (NEMA) other, width 90mm, height 170mm, depth 165mm, SIRIUS compact starter reversing starter 400 V AC/DC 110...240 V 50...60 Hz 8...32 A IP20 Main circuit connection: Screw connection Control circuit connection: Screw connection SIRIUS 3RA62 compact starter for direct starting of three-phase standard motors up to 32 A. The devices combine the functions of circuit breakers, contactors and electronic overload relays and have a very high level of operational reliability. A small variance simplifies the logistics. The compact design saves space in the control cabinet. Thanks to detachable clamps, easy replacement is possible. The devices are approved worldwide (eg IEC and UL/CSA). The compact starters are available as direct or reversing starters and are available with different setting ranges. Designed for AC/DC operation, they are available with screw-type spring-type terminals or without terminals. In addition to the communication connection via AS-Interface, the 3RA68 infeed system and auxiliary contacts and terminals are available as accessories. Simple, efficient, alway

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION *Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

