



## NH000, NH00-Fuse switch disconnector 32A 3KF1403-4LB11

**Siemens**  
3KF1403-4LB11  
4001869547596 EAN/GTIN

**1133,78 CNY** excl. VAT\*\*  
plus shipping

 15-16 days\* (CHN)

Switch disconnector with fuse 32A 3KF1403-4LB11 Design as a main switch Design as a maintenance/repair switch Design as a safety switch Design as an EMERGENCY STOP device Max. rated operational voltage Ue at AC 690V Rated uninterrupted current Iu 32A Rated uninterrupted current at AC-21, 400 V 32A, rated short-time withstand current Icw 2.5kA, rated operational power at AC-23, 400 V 15kW, switching capacity at 400 V 15kW, number of poles 4, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as changeover contact 4, device design built-in device Fixed installation technology, Suitable for floor mounting, Suitable for distributor installation, Suitable for intermediate installation, Color of the operating element other, Design of the operating element without, Connection type main circuit box terminal, Degree of protection (IP), on the front IP20, Degree of protection (NEMA) other, Load-break switch with fuse 32A, Size 1, 4-pin for NH fuse size. 000 left side panel drive basic device without handle box terminal switch disconnector with fuses 3KF as main, EMERGENCY OFF or repair switch. Depending on their size, 3KF switch disconnectors with fuses enable a rated current of between 32 and 800 A to be switched on and off. They also provide a safety isolating function in all low-voltage circuits. 3KF switch disconnectors with fuses are optimized for demanding applications in which LV HRC fuses are used. 1. Load-break switches that can be used variably with door coupling or direct drive in five sizes. 2. Simple retrofitting of functions thanks to extensive accessories. 3. Reliable protection against electrical accidents through locking functionality, contact protection and automatically locking fuse cover when switched on. 4. Robust technology with high short-circuit strength for high system availability. 5. Fast mounting on the DIN rail for sizes up to 80 A. 6. Efficient engineering with extensive CAx data. 7. Reliable protection also for wind turbines up to 690 V + 10%. For the safe, efficient electrical infrastructure in buildings and industry, Siemens offers an integrated portfolio of protective switching, measuring and monitoring devices, distribution systems, switches and socket outlets.

### YOUR ADVANTAGES

 **WORLDWIDE TRADE**  
Corporate video eibmarkt®

 **COMPLAINTS HANDLING**  
Obliging and 100% safely

 **SHORT DELIVERY TIME**  
Warehousing

 **99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide

 **25 YEARS OF EXPERIENCE**  
In worldwide mail order

 **REFUND**  
Within 14 days

 **DHL TRACK & TRACE**  
Shipment tracking

 **ORDER LIVE CHAT**  
With order history

 **DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

