



Load-break switch with fuse 125A - NH000, NH00-Fuse switch disconnecter 3KF2312-0NR11



Siemens
3KF2312-0NR11
 4001869547626 EAN/GTIN

1318,65 CNY excl. VAT**
 plus shipping



15-16 days* (CHN)

Load-break switch with fuse 125A 3KF2312-0NR11 Design as a main switch Design as a maintenance/repair switch Design as a safety switch Design as an EMERGENCY STOP device Max. rated operational voltage Ue at AC 690V Rated uninterrupted current Iu 125A Rated uninterrupted current at AC-21, 400 V 125A, rated short-time withstand current Icw 5kA, rated operational power at AC-23, 400 V 55kW, switching capacity at 400 V 55kW, number of poles 3, number of auxiliary contacts as NC contact 6, number of auxiliary contacts as NO contact 6, number of auxiliary contacts as changeover contact 3, device type built-in device fixed installation technology, Suitable for floor mounting, color of the actuating element other, design of the actuating element without, connection type main circuit other, degree of protection (IP), front IP00, degree of protection (NEMA) other, load-break switch with fuse 125A, size 2, 3-pole for NH fuse GR. 000 and 00 Front drive in the middle Basic device without handle Rear flat connection 3KF switch disconnectors with fuses as main, EMERGENCY STOP or repair switches. Depending on their size, 3KF switch disconnectors with fuses enable a rated current of between 32 and 800 A to be switched on and off. They also provide a safety isolating function in all low-voltage circuits. 3KF switch disconnectors with fuses are optimized for demanding applications in which LV HRC fuses are used. 1. Load-break switches that can be used variably with door coupling or direct drive in five sizes. 2. Simple retrofitting of functions thanks to extensive accessories. 3. Reliable protection against electrical accidents through locking functionality, contact protection and automatically locking fuse cover when switched on. 4. Robust technology with high short-circuit strength for high system availability. 5. Fast mounting on the DIN rail for sizes up to 80 A. 6. Efficient engineering with extensive CAx data. 7. Reliable protection also for wind turbines up to 690 V + 10%. For the safe, efficient electrical infrastructure in buildings and industry, Siemens offers an integrated portfolio of protective switching, measuring and monitoring devices, distribution systems, switches and socket outlets.

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

