


Item Number EB17006224

https://www.eibabo.cn/siemens/load-break-switch-with-fuse-800a-nh2-nh3-fuse-switch-disconnector-80 0a-3kf5380-2lf11-eb17006224



Load-break switch with fuse 800A - NH2, NH3-Fuse switch disconnector 800A 3KF5380-2LF11

×

Siemens

3KF5380-2LF11 4001869536644 EAN/GTIN

9023,66 CNY excl. VAT**

plus **shipping**



15-16 days* (CHN)

Switch disconnector with fuse 800A 3KF5380-2LF11 version as a main switch, version as a maintenance/repair switch, version as a safety switch, max AC-23, 400 V 400kW, switching capacity at 400 V 400kW, number of poles 3, number of auxiliary contacts as NC contact 8, number of auxiliary contacts as NO contact 8, number of auxiliary contacts as changeover contact 0, device design built-in device fixed installation, suitable for floor mounting, color of the actuating element grey, Design of the actuating element other, lockable, connection type main circuit other, degree of protection (IP), front IP00, degree of protection (NEMA) other, switch disconnector with fuse 800A, size. 5, 3-pin for NH fuse size. 2 and 3 front drive on the left Complete device with direct drive, gray flat terminal 3KF switch disconnectors with fuses as main, EMERGENCY-STOP or repair switches. Depending on their size, 3KF switch disconnectors with fuses enable a rated current of between 32 and 800 A to be switched on and off. They also provide a safety isolating function in all low-voltage circuits. 3KF switch disconnectors with fuses are optimized for demanding applications in which LV HRC fuses are used. 1. Loadbreak switches that can be used variably with door coupling or direct drive in five sizes. 2. Simple retrofitting of functions thanks to extensive accessories. 3. Reliable protection against electrical accidents through locking functionality, contact protection and automatically locking fuse cover when switched on. 4. Robust technology with high short-circuit strength for high system availability. 5. Fast mounting on the DIN rail for sizes up to 80 A. 6. Efficient engineering with extensive CAx data. 7. Reliable protection also for wind turbines up to 690 V + 10%. For the safe, efficient electrical infrastructure in buildings and industry, Siemens offers an integrated portfolio of protective switching, measuring and monitoring devices, distribution systems, switches and socket outlets.

YOUR ADVANTAGES



WORLDWIDE TRADE Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- * Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

