


**Contactor 400V - Magnet contactor 9A 24...34VDC
3RT2016-2XB42-0LA2**

Siemens
3RT2016-2XB42-0LA2
4047621016092 EAN/GTIN

462,31 CNY excl. VAT**
plus shipping


15-16 days* (CHN)

Contactor 400V 3RT2016-2XB42-0LA2 Rated control supply voltage U_s at DC 24...34V, type of voltage for actuation DC, rated operational current I_e at AC-1, 400 V 22A, rated operational current I_e at AC-3, 400 V 9A, rated operational power at AC-3, 400 V 4kW, rated operational current I_e at AC-4, 400 V 8.5A, rated operational power at AC-4, 400 V 4kW, rated operational power NEMA 3.67749375kW, suitable for series installation, number of auxiliary contacts as NC contact 1, connection type main circuit spring-loaded connection, number of NC contacts as main contacts 0, number of NO contacts as main contacts 3, railway contactor, AC-3 9 A, 4 kW / 400 V 1 NC, DC 24-34 V, 0.7-1.25* US with integrated varistor size S00, spring-loaded connection suitable for PLC outputs SIRIUS 3RT2 power contactor for switching motors under extreme conditions, eg for railway applications. The 3RT2 contactors are part of the SIRIUS modular system with its perfectly matched products. They impress with their high performance combined with a compact design and high contact reliability. They can be combined with other components in the load feeder in a variety of ways. Many of the device combinations are tested at the factory. The contactors offer the optimal connection to the controller for every application (parallel, via ASi or IO-Link). Integrated auxiliary switches reduce the complexity of your structure. The front connections enable easy wiring. The 3RT2 contactors are climate-proof, approved worldwide (eg IEC and UL/CSA) and IE3/IE4ready. This variant is characterized by an extended working and temperature range for tougher environmental conditions. They are available in various sizes and in a large power range with AC and DC operation. In addition to screw connection technology, the devices are also consistently available with spring-loaded connections for a fast, maintenance-free and vibration-proof connection. The comprehensive range of accessories, such as auxiliary switches, auxiliary releases, etc. is the same for all sizes. The available link modules, function modules and the SIRIUS 3RV29 infeed system significantly reduce the wiring effort. Simple, efficient, always up-to-date - the SIRIUS modular system.

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online
