×



https://www.eibabo.cn/siemens/circuit-breaker-3va2-iec-frame-400-3va2340-5jq42-0bc0-eb17020800



Circuit breaker 3VA2 IEC Frame 400 3VA2340-5JQ42-0BC0

Item Number

Siemens

3VA2340-5JQ42-0BC0 4042949069997 EAN/GTIN

21461,67 CNY excl. VAT**

plus shipping



15-16 days* (CHN)

Circuit breaker 3VA2 IEC Frame 400 3VA2340-5JQ42-0BC0 Rated uninterrupted current Iu 400A, rated voltage 690 ... 690V, rated limiting short-circuit breaking current Icu at 400 V, 50 Hz 55kA, overload release current setting 160 ... 400A, setting range of the short-time delayed short-circuit release 240 ... 4000A, setting range of the instantaneous short-circuit release 600 ... 4000A, connection type main circuit screw connection, device design built-in device fixed installation, suitable for DIN rail mounting, DIN rail mounting optional, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as changeover contact 2, with undervoltage release, number of poles 4, position of the connection for the main circuit at the front, design of the toggle lever actuating element, complete device with protective unit, optional motor drive, degree of protection (IP) IP40, circuit breaker 3VA2 IEC Frame 400 switching capacity class M Icu=55kA @ 415V 4-pole, system protection ETU560, LSIG, In=400A overload Protection Ir=160A...400A Short-circuit protection Isd=0.6...10 x In, Ii=1.5 x In N-conductor protection adjustable (OFF, up to 100%) Ground fault protection, switchable Ig=0.2... 1 x In= tg=0.05-0.8s Screw flat connection Undervoltage release (UVR) 24V DC 2 auxiliary switches HQ molded case circuit breakers 3VA2 with ETU 5 series for system protection. The 3VA molded case circuit breakers from Siemens, as an important part of the SENTRON protective components for industrial applications and for applications in the infrastructure sector, offer effective starter and motor protection for systems through safe shutdown in the event of overload and short circuits. The 3VA molded case circuit breakers set standards in terms of flexibility and modular variety of accessories. Uniform accessories for several sizes across all series of 3VA1 and 3VA2 molded case circuit breakers. This variant of the 3VA molded case circuit breaker is primarily characterized by: 1.Compact design. 2. Available as a variant for system protection and generator protection. 3. Available in 3 and 4 pole versions. 4. Four switching capacity classes from 55 kA ... 150 kA at 415 V. 5. Depending on the size: rated current 25 A...630 A. 6. Installation in permanent, plug-in technology, slide-in technology possible. 7. Outstanding selective protective behavior in the rated operating current distance 1:2.5 and 1:1.6, 8. The series has an electronic overcurrent release, 9. Has an integrated display for showing the measured values, 10. Optional communication connection via Modbus TCP, Modbus RTU,...

YOUR ADVANTAGES



WORLDWIDE TRADE Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

