

Item Number EB12302739

https://www.eibabo.cn/eaton/position-switch-1no-1nc-adjustable-rotary-lever-switch-ip65-ls-11s-rla-m1 2a-eb12302739



Position switch 1NO+1NC - Adjustable rotary lever switch IP65 LS-11S/RLA-M12A

×

Eaton

LS-11S/RLA-M12A 178143 4015081734665 EAN/GTIN

314,30 CNY excl. VAT**

plus shipping



15-16 days* (CHN)

Position switch 1NO+1NC LS-11S/RLA-M12A Sensor width 31mm, sensor diameter 0mm, sensor height 86mm, sensor length 33.5mm, rated operational current le at AC-15, 24 V 6A, rated operational current le at AC-15, 125 V 6A, rated operational current le at AC-15, 230 V 6A, rated operational current le at DC-13, 24 V 3A, rated operational current le at DC-13, 125 V 0.6A, rated operational current le at DC-13, 230 V 0, 3A, switching function snap-action contact, positive opening, number of safety-related auxiliary contacts 1, number of contacts as NC contacts 1, number of contacts as change-over contacts 0, version of the interface without, version of the interface for safety-related communication without, cuboid housing design , material of the housing plastic, coating housing other, design of the actuating element adjustable swivel lever, alignment of the actuating element other, design of the electrical connection other, Geei magnet for safety functions, explosion protection category for gas without, explosion protection category for dust without, ambient temperature during operation 25 ... 70°C, degree of protection (IP) IP65, degree of protection (NEMA) 4X, position switch, basic function: position switch, safety Position switch, type identifier: LS(M)-..., assortment: adjustable roller lever, degree of protection: IP66, scope of delivery: with integrated M12 connector, equipment: complete device, ambient temperature: -25 - +70°C, snap-action contact element: yes, contacts S = NO contact: 1 NO, contacts NC = NC contact: 1 NC, note: = safety function, with positive opening according to IEC/EN 60947-5-1, positive opening (ZW): yes, housing cover color: yellow, housing: plastic, connection trype: cage clamp, Cage-Clamp is a registered trademark of Wago Kontakttechnik, 32432 Minden., Accessories for the Cage-Clamp connection from Wago: Insertion bridge, grey, Wago order no. 264-402, standards and regulations: IEC/EN 60947

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®




COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE *In worldwide mail order*



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

