

Item Number EB15715277

https://www.eibabo.cn/abb/rcbo-6ka-1p-n-earth-leakage-circuit-breaker-c6-0a-ds201a-c6-0-03ap-r-eb15715277



RCBO 6kA, 1p+N - Earth leakage circuit breaker C6/0A DS201A-C6/0,03AP-R

×

ABB

DS201A-C6/0,03AP-R 2CSR255480R1064 8012542326212 EAN/GTIN

1141,39 CNY excl. VAT**

plus shipping



15-16 days* (CHN)

RCBO 6kA, 1p+N DS201A-C6/0.03AP-R number of poles (total) 2, number of fused poles 1, rated voltage 230V, rated current 6A, rated residual current 0A, residual current type other, rated breaking capacity according to EN 61009 6kA, rated breaking capacity according to IEC 60947-2 10kA, surge current strength 3kA, type of voltage AC, frequency 50/60 Hz, tripping characteristic C, switching neutral conductor, overvoltage category 3, degree of pollution 2, ambient temperature during operation 55... 55°C, width in modular units 2, Installation depth 69mm, degree of protection (IP) IP2X, FI/LS switches (RCBOs) offer personal and property protection as well as protection against electrically ignited fires in accordance with DIN VDE 0100-410 and DIN VDE 0100-530. They ensure protection of single-phase circuits against overload and short-circuit currents, protection against sinusoidal alternating currents and pulsating currents with a smooth DC residual current component of up to 6 mA to earth. As well as fault protection (protection against indirect contact), additional protection (with I n less than or equal to 30 mA) and fire protection (with I n less than or equal to 300 mA). They meet the product standards IEC/EN 61009-1 (VDE 0664-20), IEC/EN 61009-2-1 (VDE 0664-21). Areas of application are household, commercial and industrial applications. The extensive range of accessories offers you everything you need for your installation tasks. Numerous approvals make the DS201 fit for worldwide use. Optimum compromise between security and service continuity thanks to the interference immunity with surge current resistance (surge current shape 8/20 s) = 3,000 A against unwanted tripping and 10 ms short-time delay. Rated switching capacity according to IEC/EN 61009 Icn = 6 kA. RCBO DS201 A Type A AP-R is 1-pole protected (LS), 2-pole switching.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

