

F:T.N

中 SW-50

* 25A ACT

CMUC24/25-22

A2 86

×

https://www.eibabo.cn/eaton/installation-contactor-24vac-dc-3no-1nc-25a-cmuc24-25-31-eb17709380

Installation contactor 24VAC/DC, 3NO+1NC, 25A CMUC24/25-31

Eaton CMUC24/25-31 137400 4015081341825 EAN/GTIN

599,04 CNY excl. VAT**

plus shipping

馬 👘 15-16 days* (CHN)

Installation contactor 24VAC/DC, 3NO+1NC, 25A CMUC24/25-31 rated operating voltage 440 ... 440V, rated operating current 25A, utilization category 0, rated operating voltage 24 ... 24V, voltage type of the operating voltage AC/DC, voltage type of the operating voltage AC/DC, number of contacts as NO contact 3, number of contacts as NC contact 1, max. incandescent lamp load 3000W, max. fluorescent lamp load 1360VA, max. fluorescent lamp load (duo circuit) 2552VA, max. 5mm, additional equipment possible, degree of protection (IP) IP20, installation contactor, 24VAC/DC, 3NO+1NC, 25A

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL). ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU. *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

