



**Wall cabinet empty 4FB, 7 rows - Distribution cabinet (empty) 1100x1050mm A47D**



**Striebel & John**

A47D

2CPX052103R9999

4011617521037 EAN/GTIN

**6233,96 CNY** excl. VAT\*\*  
plus shipping bulky item



15-16 days\* (CHN)

Wall cabinet empty 4FB, 7-row A47D Type of installation on-wall, type of cover door, version cover with cut-out, with lock, rated current (In) 250A, height 1100mm, width 1050mm, depth 215mm, installation depth 190mm, inner depth 207mm, material thickness housing 0.9mm, Door/cover material thickness 0.9mm, color white, RAL number 9016, number of modules 336, number of rows 7, width in modular units 48, number of openings for flange plates 4, mounting option, number of cable entries 204, housing material sheet steel /Plastic, powder-coated surface, suitable for lightning protection, protection class (IP) IP54, protection class (NEMA) other, protection class II, impact resistance IK07, functional integrity without, The wall cabinets in the ComfortLine-A (D) series without interior installation are for surface mounting, flush mounting and designed for partially recessed assembly. The distributors are used, for example, in the interior of residential and industrial buildings. The housings are delivered with a door and have a variety of cable entry options in the upper or lower connection compartment. There is plenty of space on the side for cable entry and routing. A generous membrane flange is mounted at the top for each field width, with which the cables can be inserted easily, quickly and safely. Another advantage is the wide door opening angle of 120°. Furthermore, the doors can be easily removed if required and adjusted using the stepless door hinge. Thanks to the QMS snap-in technology, the expansion with meter distribution panels, combination sets, CombiLine modules or EDF mounting frames can be implemented individually according to customer requirements. Due to the flat design, the distributor can be integrated very well into any environment. The housings meet protection class IP54 and have a VDE test mark. Applicable standards: DIN VDE 0603-1, DIN 43870-1, color white RAL 9016 and powder-coated.

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

