

**LED built-in wallwasher 4000K 80° white -
Downlight/spot/floodlight 1x59W VFCL 7005540 ws****LTS**
VFCL 7005540 ws
648578
4043544559883 EAN/GTIN**1391,42 CNY** excl. VAT**
plus shipping

15-16 days* (CHN)

LED built-in wallwasher 4000K 80° white VFCL 7005540 ws Suitable for built-in installation, adjustability swivelling, LED bulbs not replaceable, with bulbs, suitable for number of bulbs 1, other socket, housing material aluminium, other surface, housing color white, cover material glass transparent, voltage type AC, nominal voltage 220 ... 240V, nominal LED current at constant current 1050 ... 1050mA, electronic ballast, without dimming function, highly specular reflector, reflector light distributor, light distribution asymmetrical, beam angle wide beam 41-80°, light emission direct, energy efficiency index (EEI) of the power supply other, protection class (IP) IP20, protection class (NEMA) other, protection class III, suitable for lamp power 59 ... 59W, max. system power 59W, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, rated luminous flux according to IEC 62722-2-1 5720lm, lamp luminous efficacy 96.94lm/W, width 168mm, height/depth 137mm, length 238mm, installation width 150mm, installation height/depth 135mm, installation length 210mm, type of wiring termination, connection type other, light with limited surface temperature "D mark", light output 96.94lm/W, photobiological safety according to EN 62471 other, color consistency (McAdam Ellipse) SDCM3, built-in wallwasher with asymmetrical light distribution for uniform illumination of vertical surfaces, lamp unit can be swiveled out by 40° (infinitely variable position locking), easy installation/removal of the lamp unit using spring clips, high maintenance friendliness, no UV and heat radiation, heat management with passive cooling (heat sink off aluminium), reflector with hammer finish optics made of pure aluminium for very high light output, luminaire unit made of aluminium, mounting frame made of sheet steel, tool-free ceiling installation with quick-action clamping springs (automatic adjustment of the ceiling thickness), clear protective glass (easy to open with a locking screw), connection to control gear via luminaire cable with min I-Clamp plug connection, control gear (LED converter) included (external placement)

YOUR ADVANTAGES**WORLDWIDE TRADE**
Corporate video eibmarkt®**99% CUSTOMER SATISFACTION**
> 500,000 customers worldwide**DHL TRACK & TRACE**
Shipment tracking**COMPLAINTS HANDLING**
Obliging and 100% safely**25 YEARS OF EXPERIENCE**
In worldwide mail order**ORDER LIVE CHAT**
With order history**SHORT DELIVERY TIME**
Warehousing**REFUND**
Within 14 days**DATA PROTECTION**
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

