

https://www.eibabo.cn/ledvance/led-floodlight-4000k-sw-downlight-spot-floodlight-flpfm20w4000ksym1 00b-eb13262440



## LED floodlight 4000K sw - Downlight/spot/floodlight FLPFM20W4000KSYM100B

## **LEDVANCE**

FLPFM20W4000KSYM100B 4058075421011 4058075421011 EAN/GTIN

108,12 CNY excl. VAT\*\*

plus shipping



4-5 days\* (CHN)

LED floodlight 4000K sw FLPFM20W4000KSYM100B Energy efficiency class of the built-in light source A++, A+, A (LED), Suitable for surface mounting, Suitable for wall mounting, Adjustability swivelling, Light source LED not replaceable, With light source, Material of the housing aluminium, Surface powder-coated, Housing color black, Cover material opal glass, type of voltage AC, nominal voltage 100... 277V, nominal LED current at constant current 98... 98mA, ballast electronic ballast, with ballast, without dimming function, reflector without, light distributor reflector, beam angle unshielded/diffuse, light emission direct, Distortion factor (THD) 19, rated service life L70/B10 at 25 °C 70000h, rated service life L70/B50 at 25 °C 70000h, rated service life L90/B50 at 25 °C 70000h, rated service life L90/B50 at 25 °C 35000h, degree of protection (IP) IP65, impact resistance IK07, protection class I, rated ing ambient temperature according to IEC62722-2-1-30... 50°C, max. system power 20W, light color white, color temperature 4000... 4000K, color rendering index CRI 80-89, luminous flux 2400... 2400lm, rated luminous flux according to IEC 62722-2-1-2400lm, lamp efficacy 120lm/W, power factor 0.9, width 156mm, height/depth 42mm, length 144mm, type of wiring termination, number of poles 3, connection type other, luminous efficacy 120lm/W, glow wire test according to IEC 60695-2-11 650 °C - 30 s, photobiological safety according to EN 62471 RG1, color consistency (McAdam ellipse) SDCM5, versatile floodlight with 20 W power consumption. Product features: Reflector-based, symmetrical light distribution with a beam angle of 100° x 100°. Integrated ballast with a wide input voltage range, suitable for 100 - 277 VAC. Surge protection: up to 4kV (L/N-PE), 2kV (LN). Mounting bracket with 30° angle and large rotation range. Pre-installed, flexible cable (H05RN-F) with 1 m length, 3 x 1.0 mm² crimped. Product advantages: bright, robust and durable. Safe and very even illumination thanks to the opal, hardened glass diffuser. N

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



**25 YEARS OF EXPERIENCE** *In worldwide mail order* 



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



**DATA PROTECTION** *Guarantee* 

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online



