
×



## Item Number EB18803719

https://www.eibabo.cn/zumtobel/led-wallwasher-4000k-ceiling-wall-luminaire-sui-df9-60211007-eb1880 3719



## LED wallwasher 4000K - Ceiling-/wall luminaire SUI DF9 #60211007

## Zumtobel

SUI DF9 #60211007 60211007 4053167363118 EAN/GTIN

3458,66 CNY excl. VAT\*\*

plus shipping



15-16 days\* (CHN)

LED wallwasher 4000K SUI DF9 60211007 Suitable for ceiling mounting, Suitable for recessed mounting, LED bulbs cannot be replaced, With bulbs, Suitable for number of bulbs 1, Other socket, Housing material aluminium, Housing color black, Cover material plastic opal, Design of the louvre without, Type of voltage AC, Rated voltage 220 ... 240V, Control gear LED control gear, current-controlled, With control gear, Dimming DALI, Light distribution asymmetrical, Light emission direct, Rated service life L70/B50 at 25 °C 100000h, Rated service life L80/B50 at 25 °C 100000h, Rated service life L90/B50 at 25 °C 50000h, degree of protection (IP) IP20, protection class II, glow wire test according to IEC 60695-2-11 850 °C - 30 s, max. system power 30W, rated luminous flux according to IEC 62722-2-1 1499lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 90-100, power factor 0.97, width 50mm, height/depth 54mm, length 335mm, installation length 323mm, installation width 39mm, egg Installation height/depth 100mm, compact, linear LED recessed ceiling light as a wallwasher with patented, miniaturized free-form liteCarve(R) reflector technology, for brilliant and evenly asymmetrical illumination of vertical surfaces, starting from an LED point light source, the liteCarve(R) reflector directs the Light that is 100% indirect, targeted and free of stray light on the vertical surface, with 9 miniaturized individual light heads in a linear arrangement, fitted with: 30W LED1500-940, WALLWASHER radiation characteristics, reflector: silver with black decorative edge, highly specular, color rendering index Ra > 90, color temperature 4000 K (neutral white), color location tolerance (initial MacAdam): 2, luminous flux of luminaire: 1499 lm, luminous efficacy of luminaire: 50 lm/W, service life: 50000h at 90% luminous flux, complete model consisting of luminaire and separate ballast unit, DALI controllable luminaire (DALI only), passive cooling through innovative heat management, housing made of die-cast al

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

