



Soft starter Sirius 400V, 40 degrees 200AC - Soft starter 45A 110...230VAC 3RW3036-2BB14



Siemens
3RW3036-2BB14
 4011209719330 EAN/GTIN

4539,22 CNY excl. VAT**
 plus shipping



15-16 days* (CHN)

Soft starter Sirius 400V, 40 degrees 200AC 3RW3036-2BB14 Rated operational current I_e at 40 °C Tu 45A, rated operational voltage U_e 200... 480V, rated power three-phase motor, standard circuit, at 230 V 11kW, rated power three-phase motor, standard circuit, at 400 V 22kW, function one direction of rotation , rated ambient temperature without derating 40°C, rated control supply voltage U_s at AC 50 Hz 110... 230V, rated control supply voltage U_s at AC 60 Hz 110... 230V, rated control supply voltage U_s at DC 110... 230V, type of voltage for actuation AC/DC, degree of protection (IP) IP00, The Sirius 3RW30 soft starters reduce the motor voltage through variable phase control and ramp it up from an adjustable starting voltage to mains voltage. These devices limit both current and torque during run-up and avoid the shocks that occur with direct or star-delta starting. Mechanical loads and mains voltage dips can be reliably reduced in this way. The gentle start-up protects the connected devices and ensures a longer trouble-free production process with less wear. Due to the adjustable start value of the voltage, the soft starters can be set individually to the requirements of the application and, unlike star-delta starters, are not tied to two-stage starting with fixed voltage ratios. The Sirius 3RW30 soft starters are characterized above all by their small space requirements. Integrated bridging contacts avoid having to accept power losses at the power semiconductors (thyristors) after the motor has started up. This saves heat losses, allows for a more compact design and makes external bypass circuits superfluous. Note: When switching on three-phase motors, there are usually voltage dips with all types of start (direct start, star-delta start, soft start). The infeed transformer must always be dimensioned in such a way that the voltage dip when the motor is started remains within the permissible tolerance. If the infeed transformer is tightly dimensioned, the control voltage (independent of the main voltage) should be supplied from a separate circuit to prevent the soft starter from switching off

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

