

Item Number EB16200702

19.04.2024/03:05

×

https://www.eibabo.cn/siemens/soft-starter-sirius-55kw-400v-24v-soft-starter-106a-24vac-24vdc-3rw40 47-2bb04-eb16200702



Soft starter Sirius 55kW/400V,24V - Soft starter 106A 24VAC 24VDC 3RW4047-2BB04

Siemens 3RW4047-2BB04 4011209696556 EAN/GTIN

9599,35 CNY excl. VAT**

plus shipping

I5-16 days* (CHN)

Sirius soft starter 55kW/400V,24V 3RW4047-2BB04 Rated operational current le at 40 °C Tu 106A, rated operational voltage Ue 200 ... 480V, rated power three-phase motor, standard circuit, at 230 V 30kW, rated power three-phase motor, standard circuit, at 400 V 55kW, function one direction of rotation , Rated ambient temperature without derating 40°C, Rated control supply voltage Us at AC 50 Hz 24 ... 24V, Rated control supply voltage Us at AC 50 Hz 24 ... 24V, Rated control supply voltage Us at AC 60 Hz 24 ... 24V, Rated control supply voltage Us at DC 24 ... 24V, Type of voltage for actuation AC/DC, integrated Motor overload protection, degree of protection (IP) IP00, SIRIUS S3 soft starter 106 A, 55 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC Spring-loaded terminals SIRIUS 3RW40 soft starter for standard applications for smooth starting and stopping of three-phase asynchronous motors . Infinitely variable starting, reduction of current peaks, avoidance of mains voltage fluctuations during start-up, relief of the power supply network, reduction of the mechanical load in the drive, considerable space and wiring savings compared to star-delta starters and frequency converters, maintenance-free switching and extremely easy handling. The integrated bypass enables the very compact design and ensures less heating in the control cabinet. Intelligent monitoring functions protect the soft starter from overheating and the motor from overload. In addition, you can limit the current during startup to an adjustable maximum value. With the integrated remote reset, you can quickly and easily fix faults remotely. Worldwide approvals (eg IEC and UL/CSA) also for potentially explosive applications (ATEX or IEC Ex). The 3RW soft starters are available for supply systems up to 690 V in a large power range with different control supply voltages and consistently with screw and spring-type terminals. For 3RW30/40 there are additional versions with 24 V control supply voltage. Some of the 3RW40 up to size S3 and all 3RW44 also offer ther

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

