

**LED mounted light 3000K,3500K,4000K - Ceiling-/wall luminaire LENA VARIO #96631864****Zumtobel**  
LENA VARIO #96631864  
96631864  
9010299044938 EAN/GTIN**320,15 CNY** excl. VAT\*\*  
plus shipping

4-5 days\* (CHN)

LED surface-mounted luminaire 3000K,3500K,4000K LENA VARIO 96631864 Suitable for wall mounting, Color temperature can be switched in steps, Suitable for surface mounting, Light source LED cannot be replaced, With light source, Suitable for number of light sources 1, Other socket, Housing material plastic, Housing color white, Material of the cover plastic opal, design of the louvre without, voltage type AC, nominal voltage 200 ... 240V, control gear current-controlled LED control gear, with control gear, without dimming function, light distribution symmetrical, beam angle extremely wide beam >80°, light emission direct, rated service life L70/B50 at 25 °C 50000h, rated service life L80/B50 at 25 °C 33000h, rated service life L90/B50 at 25 °C 16000h, degree of protection (IP) IP44, impact resistance IK04, protection class II, rated ambient temperature according to IEC62722-2-1 -20 ... 40 °C, glow wire test according to IEC 60695-2-11 650 °C - 30 s, max. system power 21W, rated luminous flux according to IEC 62722-2-1 1950lm, Li Real color white, color temperature 3000 ... 4000K, color rendering index CRI 80-89, luminous efficacy of luminaire 93lm/W, power factor 0.9, height/depth 115mm, outer diameter 410mm, type of wiring suitable for through-wiring, conductor cross-section 2.5mm², connection type plug-in terminal, round Wall and ceiling light (IP44) with switchable color temperature: choice between warm white (3000 K) and neutral white (3500 K or 4000 K) depending on the application. High-quality PMMA diffuser for even light distribution. Reliable integrated LED technology that ensures maintenance-free installation and a long service life. Direct replacement for 2 x 26W and over 55% energy savings compared to fixtures with CFL lamps. Plug-in terminal for cables up to 2.5 mm². Quick and easy installation. Through wiring possible. Flicker free and DC compatible. Backplate: steel, white. Diffuser: opal, PMMA. Weight: 0.83kg

**YOUR ADVANTAGES****WORLDWIDE TRADE**  
*Corporate video eibmarkt®***99% CUSTOMER SATISFACTION**  
*> 500,000 customers worldwide***DHL TRACK & TRACE**  
*Shipment tracking***COMPLAINTS HANDLING**  
*Obliging and 100% safely***25 YEARS OF EXPERIENCE**  
*In worldwide mail order***ORDER LIVE CHAT**  
*With order history***SHORT DELIVERY TIME**  
*Warehousing***REFUND**  
*Within 14 days***DATA PROTECTION**  
*Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop  
**eibabo®** electronics cheap online order  
**eibabo®** electric appliances buy online

