

F:T.N

2311 ~ 500;

Z-SCH230/25-40

6 8(14)

 $U_i = 840V - I_R = 25A A C I$

×

https://www.eibabo.cn/eaton/installation-contactor-230vac-2-no-0-nc-z-sch230-40-20-eb15624012

Installation contactor 230VAC 2 NO/ 0 NC Z-SCH230/40-20

Eaton

Z-SCH230/40-20 248855 4015082488550 EAN/GTIN

655,16 CNY excl. VAT**

plus shipping

https://www.actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actional.com/actiona

Installation contactor 230VAC 2 NO/ 0 NC, Installation contactor 230VAC 2 NO/ 0 NC Rated operating voltage 440 ... 440V, Rated operation current 40A, Utility category 1, Rated excitation voltage 230 ... 230V, Voltage type (operating voltage) AC, Voltage type (excitation voltage) AC, Number of contacts as normally open contact 2, Number of contacts as normally closed contact 0, Max. incandescent lamp load 5520W, Max. load fluorescent lamp 2610VA, Max. load fluorescent lamp (Duo circuit) 5336VA, Max. load fluorescent lamp (parallel compensated) 2088VA, Number of modular spacings 3, Built-in depth 60mm, Additional equipment possible, Degree of protection (IP) IP40

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL). ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU. *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

