



## Input module digital - Fieldbus digital module 20 In / 0 Out XN-322-20DI-PF



**Eaton**  
**XN-322-20DI-PF**  
 178768  
 7640130098329 EAN/GTIN

**1009,82 CNY** excl. VAT\*\*  
 plus shipping

 15-16 days\* (CHN)

Supply voltage at AC 50 Hz 0 V, Supply voltage at AC 60 Hz 0 V, Supply voltage at DC 18..30 V, Voltage type of the supply voltage DC, Number of digital inputs 20, Digital inputs configurable no, Digital outputs configurable no, Input current at signal 1 3.7mA, Permissible voltage at the input 30 V, Type of input voltage DC, Type of digital output without, Output current 0A, Permissible voltage at the output 0 V, Type of output voltage DC, Short-circuit protection, outputs available no, Number of HW interfaces other 1, With optical interface no, Supports protocol for TCP / IP no, Supports protocol for PROFIBUS no, Supports protocol for CAN no, Supports protocol for INTERBUS no, Supports protocol for ASI no, Supports protocol for KNX no, Supports protocol for MODBUS no, Supports data highway protocol no, Supports protocol for DeviceNet no, Supports protocol for SUCONET no, Supports protocol for LON no, Supports protocol for PROFINET IO no, Supports protocol for PROFINET CBA no, Supports protocol for SERCOS no, Supports protocol for EtherNet / IP no, Supports protocol for DeviceNet Safety no, Supports protocol for INTERBUS safety no, Supports protocol for PROFIsafe no, Supports protocol for SafetyBUS p no, Supports protocol for other bus systems yes, Wireless standard Bluetooth no, Wireless standard WLAN 802.11 no, Radio standard GPRS no, Radio standard GSM no, Radio standard UMTS no, IO-Link master no, System component yes, IP protection) IP20, Delay time with signal change 0..0,5 ms, Rail mounting possible yes, Wall / direct mounting possible no, Front installation possible no, Rack mounting possible no, Suitable for safety functions no, SIL according to IEC 61508 without, Performance level according to EN ISO 13849-1 without, Associated equipment (Ex ia) no, Associated equipment (Ex ib) no, Explosion protection category for gas without, Explosion protection category for dust without, Width 16.8 mm, Height 104.2 mm, Depth 80.3 mm

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
 Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
 > 500,000 customers worldwide



**DHL TRACK & TRACE**  
 Shipment tracking



**COMPLAINTS HANDLING**  
 Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
 In worldwide mail order



**ORDER LIVE CHAT**  
 With order history



**SHORT DELIVERY TIME**  
 Warehousing



**REFUND**  
 Within 14 days



**DATA PROTECTION**  
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop  
**eibabo®** electronics cheap online order  
**eibabo®** electric appliances buy online

